DEC 20 1919
Bureau of Standards

DECEMBER 1, 1919 PRICE 25 CENTS

AVIATION AND AERONAUTICAL ENGINEERING



The Sperry Combination Land and Sea Plane
(C) *Wide World Photos*

VOLUME VII
Number 9

SPECIAL FEATURES

PECULIARITIES IN FLYING IN THE WIND
THE LINKE-HOFFMANN GIANT AIRPLANES
DEVELOPMENT OF A 15-FT. WING RIB
STATIC HEAD TURN INDICATOR FOR AIRPLANES
AIR FANS FOR DRIVING GENERATORS ON AIRPLANES

Three Dollars a Year

PUBLISHED SEMI-MONTHLY
BY
THE GARDNER-MOFFAT CO., INC.
HARTFORD BUILDING, UNION SQUARE
12 EAST SEVENTEENTH STREET, NEW YORK

Entered as second-class matter, August 5, 1918, at the Post Office at New York, N. Y., under act of March 3, 1879



CREW OF U. S. MARTIN "ROUND THE RIM FLYER"—Left to right: Colonel Hartz, Lieuts. L. A. Smith and E. E. Harmon, Sergeants John Harding, Jr., and Jeremiah Tobias

Martin Bomber No. 2 has been in constant use for a year at Bolling Field, Washington, D. C. With more than 10,400 miles of cross country work already to its credit, this plane was started off on an 8,000 mile flight around the rim of the United States, in command of Col. R. S. Hartz. The colonel and his crew of four have just completed their unparalleled pioneering trip.

Martin airplanes have demonstrated beyond a question the greatest ton-mile efficiency of any aircraft yet produced, and are rapidly proving that the important centres of the United States can be connected by aerial transportation with but a few hours' flying.

THE FOLLOWING IS A COMPARISON OF A FEW ACTUAL FLIGHTS BY MARTIN BOMBERS WITH THE BEST RAILROAD TIME:

FROM	TO	PILOT	DISTANCE	MARTIN AIRPLANE TIME	RAILROAD TIME
Cleveland	Dayton	Eric Springer	215 Miles	1 hour, 50 min.	6 hours
Washington	New York	Capt. Francis	225 Miles	2 hours	5 hours, 15 min.
Cleveland	Washington	Eric Springer	350 Miles	2 hours, 58 min.	14 hours
Cleveland	New York	Eric Springer	450 Miles	3 hours, 20 min.	14 hours
Dayton	New York	Capt. Francis	635 Miles	6 hours, 40 min.	18 hours
Macon	Washington	Capt. Francis	630 Miles	6 hours, 15 min.	21 hours

The superiority of performance which characterizes Martin Airplanes is the result of ten years of experience in building aircraft of a superior quality

The Glenn L. Martin Co.
CLEVELAND
Contractors to the U. S. Army, Navy and Post Office Departments

The newest Vought Product, Model VE-10 3-Place Flying Boat—



¶ The unrivalled character of the Design and Performance, of course, goes without saying.

¶ We invite your attention to the Desirability of Possession—assuring you of reasonable First Cost and negligible Operating Expense.

¶ Immediate Delivery.

CHANCE M. VOUGHT
WEBSTER AND SEVENTH AVENUES
Long Island City, New York

Aéroplanes
VOUGHT

The Vought VE-7 2-Place Training and Sport Airplane—



¶ VE-7, Maj. R. W. Schroeder, U. S. A. pilot, won the New York-Toronto International Airplane Reliability Handicap Contest.

¶ Adopted by U. S. Army Air Service as the Standardized Advanced Training Type.

¶ Immediate Delivery for Civil Use.

LEWIS & VOUGHT CORP.
WEBSTER AND SEVENTH AVENUES
Long Island City, New York

FARMAN

AEROPLANES

Billancourt, (Seine), France

The FARMAN three-passenger "Tourabout"—the first French pleasure plane to arrive in America. Now being demonstrated.

H. & M. FARMAN planes have been the recognized leaders of the Aircraft Industry in France since 1907.

FARMAN planes have been flown by over 15,000 pilots, over the great capitals of America and Europe, in all kinds of weather, in Peace and in War.

H. & M. FARMAN were First in the Field in the construction of Commercial Aeroplanes with the Famous FARMAN "Goliath," making regular trips between Paris and Brussels.

FARMAN products are built for SAFETY, SERVICE and RELIABILITY, backed by the experience and knowledge gained in the manufacture of thousands of aeroplanes.

For business—Buy a FARMAN

The "Goliath"—14 Passenger (or freighter
The "Tourabout"—3 Passenger

For pleasure—Fly a FARMAN

The "Limousine"—6 Passenger (or freighter)
The "Training Plane"—2 Passenger

Deliveries at New York, planes assembled, tested, and ready for flight

Represented in America by

W. WALLACE KELLETT

1 WEST 34th ST. **NEW YORK CITY**

Aeromarine

Factory
Keyport, N. J.

New York Office
Times Bldg.

In Addition to Military and Sporting Requirements

THE AEROMARINE PLANE & MOTOR COMPANY

a complete organization of pre-war origin

Will Specialize in the Development and Production

of

Commercial Airplanes and Motors

for

The Transportation of Passengers and Freight

Our engineering department is at your service for consultation on aerial transportation problems.

We design and build propellers of walnut.

Our mills are located in the choicest walnut districts in the country, affording an unlimited supply of the best timber.

Walnut is the acknowledged superior wood for airplane propellers, government tests having shown that it is strong, durable and able to withstand great shocks.

HARTZELL WALNUT PROPELLERS

have proven by their performance that they are efficient and lasting.

Our Engineering Department will gladly co-operate with you in designing a propeller to meet your requirements.

HARTZELL WALNUT PROPELLER COMPANY

"Builders of propellers of proven performance"

DECEMBER 1, 1919

AVIATION
AND
AERONAUTICAL ENGINEERING

VOL. VII. NO. 9

Member of the Audit Bureau of Circulations

INDEX TO CONTENTS

	PAGE
Editorials	381
Explanation of Peculiarities Observed in Flying in the Wind	382
Development of a 15-Ft Wing Rib	386
Static Head Turn Indicator for Airplanes	389
The Linke-Hoffmann Central Power Plant Giant Biplanes	391
Wind Tunnel Tests of Airship Envelopes	395
Air Fans for Driving Generators on Airplanes	396
French Practice in Airship Construction	400
Air Mail Record	402

THE GARDNER - MOFFAT COMPANY, Inc., *Publishers*

HARTFORD BUILDING, UNION SQUARE, 22 EAST SEVENTEENTH STREET, NEW YORK

WASHINGTON OFFICE, EVENING STAR BUILDING

SUBSCRIPTION PRICE: THREE DOLLARS PER YEAR. SINGLE COPIES TWENTY-FIVE CENTS. CANADA, THREE AND A HALF DOLLARS: FOREIGN, FOUR DOLLARS A YEAR. COPYRIGHT 1919, BY THE GARDNER-MOFFAT COMPANY, INC.

ISSUED ON THE FIRST AND FIFTEENTH OF EACH MONTH FORMS CLOSE FIVE DAYS PREVIOUSLY. ENTERED AS SECOND-CLASS MATTER, AUGUST 3, 1916, AT THE POST OFFICE AT NEW YORK, N. Y., UNDER ACT OF MARCH 3, 1879.

AEROPLANE CRANKSHAFTS

WYMAN-GORDON COMPANY

"The Crankshaft Makers"

Worcester, Mass. Cleveland, Ohio

Quality



NOTE the angular contact of ball with raceways. Both radial and thrust loads combine and are carried through the axis of each ball. Balls are always free to roll with practically no friction. No wedging. No cramping. No binding.

FREEDOM from wedging, cramping and binding of rolling elements eliminates excessive wear in New Departure Ball Bearings. No matter from what direction loads may come, or with what intensity, the Double Row carries them with greatest ease. Friction is practically eliminated.

Bearings which are made adjustable to "take up" for wear probably need that allowance. New Departure ball bearings will operate for the full life of the machine without wearing enough to require adjustment.

THE NEW DEPARTURE MANUFACTURING COMPANY,
Bristol, Conn. 474 Detroit, Mich.

New Departure Ball Bearings

L. D. GARDNER
PRESIDENT AND EDITOR
W. D. MOFFAT
VICE-PRESIDENT
W. I. SEAMAN
TREASURER
H. M. WILLIAMS
GENERAL MANAGER

AVIATION
AND
AERONAUTICAL ENGINEERING

ALEXANDER KLEMIN
TECHNICAL EDITOR
LADISLAS D'ORCY
ASSOCIATE EDITOR
GEORGE NEWBOLD
BUSINESS MANAGER

Vol. VII | December 1, 1919 | No. 9

N a recent paper before the Insurance Society, a well known insurance man spoke of the good feeling which insurance people had as a whole towards aeronautics, and the effort they were prepared to put forth to help the industry in its initial stages. They owed it as a public duty, so Mr. Cowles thought, to take up aviation insurance even if the business were meagre and unprofitable.

Now while we appreciate the kindliness of these remarks and feel sure that the cooperation of insurance companies would be a valuable help to the industry, we rather resent the patronizing attitude. Give the industry just a little more time, and aviation insurance will be a large source of profitable income for the insurance men, and a source constantly growing. Instead of patronizing the industry, insurance companies would do better to study the subject intensively, to give a hand in seeing that certain well known precautions in structure and piloting were always observed. Their differential action in granting insurance only on certain ships, with well qualified pilots, and to entirely reputable operating companies would be extremely helpful in keeping the industry on an entirely steady basis.

British Effort in the Air

News has just arrived of the successful termination of a flight from England to Australia. On a route following Paris, Lyons, Rome, Naples, Brindisi, Sicily, Aboukir, Kantara, Damascus, Baghdad, Basra, Karachi, Delhi, Calcutta, Rangoon, Penang, Singapore, Bandoeng, Agambola and Port Darwin, more than half the ports of call are British possessions.

A similar flight might be made from the Cape to Cairo. A huge British flying boat might fly from Ireland to Canada, and be on British territory on both sides of the ocean.

There is nothing astonishing therefore that the British people as a whole, and the British Government in particular, should devote such keen attention to aerial work, and devote such large sums to its development.

As in the case of the Merchant Marine, the United States will have to meet the mighty yet almost unconscious British effort, with a determined and conscious effort.

Cockpit Design

It is interesting to see how rapidly the art of cockpit design is developing.

An interesting example is the cockpit of the Sopwith "Wallaby," designed primarily to attempt the Australian flight.

The pilot's and navigator's cockpit is fitted with Triplex side windows and a floor window in front of the pilot. Normally the seats allow the crew to sit in the usual position with their heads just clear of the cockpit, but provision is made by means of which the cockpit may be converted into an enclosed cabin, the seats being fitted with clips which allow them both to drop about a foot and sliding doors being pulled across the openings. Four of the side windows are made to open, and a pipe running from the front of the radiator supplies fresh air to the crew. Dual control is provided, and the pilot has two rudder bars one above the other, for the two seat positions. There is a system of pull-out tables for charts and slots for instruments. The circular opening for the pilot's head is fitted with an aluminum beading which is graduated off into degrees for use with a sextant. In rear of the passenger are cupboards for food.

It would seem quite possible even in a small single-engined machine to design a cockpit providing every facility for piloting and navigation, which is thoroughly comfortable and livable.

Parachutes

E. R. Calthrop, the well known designer of parachutes, suggests that the worst enemy of the parachute is the presence of projections in rear of the cockpits on which the parachute may run foul. The parachute, however well designed, is always a delicate affair, and even a small rent may cause disaster. If the tail skid in particular presented a smooth unbroken outline, there would be much less chance of accidents. Mr. Calthrop suggests very forcibly that in the design of military machines definite specifications be laid down to remove projections in rear of cockpit, and his suggestion is worth consideration, particularly in view of the authority that his experience warrants.

Water Resistant Plywood Glues

In a recent issue of AVIATION, a description is given of tests for waterproof glues developed by the Forest Products Laboratory.

To read of the rigid tests now imposed, and successfully met, is most reassuring to the airplane construction. The Forest Products Laboratory considers 8 hour boiling and ten day soaking tests as quite reasonable, with the boiling tests producing more severe damage.

Such tests, it is safe to say, are much more severe than anything that glues will have to withstand in current practice. They indicate tremendous progress since the early days of glue manufacture.

Explanation of Peculiarities Observed in Flying in the Wind

By J. G. Coffin

Assistant Director of Research, Curtiss Engineering Corporation

Considerable misconception exists in regard to the effect of wind on machines which float or fly in the air.

The misconception arises principally in not distinguishing between the speed of the machine in the air as compared to the speed of the machine relatively to the ground, and in not having a full realization of the fact that forces are only produced by changes in velocity and not by velocity itself.

A steady wind is detrimental only in so far as it reduces the ground speed when going against it, but it is also of advantage when going with it and as a matter of fact it is of benefit as far as getting off and landing is concerned with heavier than air machines as it reduces by the additional wind speed (at the ground) the getting off and landing speeds.

The getting off and landing ground speed of a plane would be zero if it headed into a wind equal in speed to the slow speed of the plane, thus avoiding the strains on the landing gear due to high relative ground speed.

An airplane flies relatively to the wind, whatever the wind velocity may be. This statement becomes evident when it is remembered that the necessary lift required for flight can only be obtained by a definite relative speed between the plane and the air for any given angle of incidence.

The atmosphere is carried around by the earth at a speed which amounts to about 750 miles per hour in this latitude. To all intents and purposes this is a wind of frightful velocity and yet no one considers it one because we are all moving with it and hence are at rest relatively to it.

What is ordinarily called a wind is a relative motion between the earth and the atmosphere above it. It is felt as a wind because everything, excepting free objects in th air, cannot move with it.



FIG. 1.

An airplane or balloon as long as it is in contact with the ground is buffeted by the wind, but very soon after it loses contact with the ground it partakes of the general wind motion. Were it not that the pilot can see his drift relatively to the ground, he would not and could not be aware of any wind excepting that produced by his own motion through the air necessary, in the case of the airplane, for sustentation. In the case of a balloon, it is always floating in calm air. These remarks refer to a uniform and steady wind only.

When the wind is unsteady or gusty entirely different phenomena arise. Changes in wind speed, especially abrupt ones, are not only distinctly felt but often produce dangerous disturbances. Changes in wind speed are, however, felt only while the change is taking place and no longer, although their effects may last for a longer period. The speed of the wind before and after the change is of absolutely no consequence, the magnitude of the disturbance depending on the rate of change of wind speed and the duration of this rate of change.

The course of an airplane relatively to the ground can always be obtained by the vectorial addition of the velocity relatively to the air and of the velocity of the air relatively to the ground. In a steady horizontal wind, as far as the plane is concerned, there should be and can be no reason for any peculiarity in its control.

As an apparent exception to this statement it is well to mention that if a pilot judges his air speed by his view of the ground, when flying in a wind, he will be misled and since he may not know the wind speed he may commit serious errors of control especially on landing and in maneuvering. This is, however, purely psychological and is not pertinent to the subject of this paper.

Now, apart from any such explanation, since it is positively asserted that peculiarities of control do occur in a steady wind that do not occur in calm air and that experienced pilots provide for them, the reasons for such provisions must be looked for elsewhere. There are two principal possibilities to consider:



FIG. 2.

1st. A vertical wind gradient exists—meaning by this that the horizontal wind speed changes with the height above the earth's surface. This change is usually an increase.

2nd. A more or less periodic horizontal variation in wind speed exists—meaning what are known as "Gusts." Case 2 is not susceptible of easy mathematical treatment* and in addition the peculiarities we are attempting to explain occur even when the wind is blowing steadily. We shall then limit ourselves to the consequences of Case 1.

In this case the air is supposed to have different horizontal velocities at different altitudes and the plane must rise or fall in order to experience the effect of any variation of wind velocity. As the pilot is continually changing his level in flight, either consciously or unconsciously when making turns, climbing, gliding, stunting or by uncontrolled changes in propeller thrust he must necessarily be subjected to such variations.

The immediate problem then reduces itself to finding the effect on the rate of climb in a wind which has a velocity increasing (say) with altitude according to some law. It is, of course, well known that at moderate altitudes the wind velocity does increase with height, the observed effect being most

FIG. 3.

naturally ascribed to friction with the earth's surface. The direction of the wind, also, can and does change. Changes in wind speed of 20 m.p.h. per 1000 ft. rise and of over 90° in direction are not unusual. We shall, however, consider that

* In regard to this see work of E. B. Wilson, Theory of an Airplane Encountering Gusts; Part I—First Annual Report of the National Advisory Committee for Aeronautics, 1915, pp. 52-75; Part II—Third Annual Report of the National Advisory Committee for Aeronautics, 1917, pp. 405-443.

merely a speed change takes place. It is also evident that the speed change per ft. rise can and does vary at different levels, but for purposes of calculation we shall assume that the wind speed increases at a uniform rate per ft. rise.

Effect of a Wind Gradient

Consider an airplane climbing with speed V along its flight path; this path making an angle i with the horizontal. Assume that the wind speed increases at a rate of "a" feet per second per ft. rise. The quantity "a" is called the vertical wind gradient.

The vertical speed of the machine is $V \sin i$ ft./sec. ..... (1)
and hence the increase in wind speed per second due to this vertical rise is $a V \sin i$ ft./sec.^{2} ..... (2)
This last expression is the acceleration in wind velocity due to



FIGS. 4-5-6-7.

a rise. This acceleration acts on the plane just as if the plane, flying originally in calm air, were to experience an increase in wind speed. It is evident that if it were facing this extra wind the result would be an improved lift, and if it were facing the other way the lift would be decreased.

There results, in other words, an apparent horizontal acceleration of the plane, which is in the *direction opposite* to the wind velocity when the plane is going from low speed wind into higher speed wind and which is in the *same direction* as the wind when going from high speed wind into lower speed wind.

This matter which is fundamental can perhaps be more easily understood by the following analogy.

Consider a number of moving platforms, Fig. 2, such as have been proposed at various time for subway transportation. Let the platforms be three feet wide and each one have a speed of 5 ft./sec. greater than the preceding one. As it is comparatively easy to step from the ground onto platform 1, it will be subsequently just as easy to step from 1 onto 2 and so on until finally the pedestrian finds himself on a platform moving at a comparatively high speed. There is an increase of 5 ft./sec. for every 3 ft. of motion across the platforms, *or* 5 *ft./sec. per* 3 *ft.* = *ft./sec. per ft.*, which number corresponds to the quantity "a" in equation (2).

If, now, one were to run around, back and forth over such a system of moving platforms it is quite evident, and would be more so on trial, that "things" are peculiar. It is just such peculiarities that a plane experiences in maneuvering in a wind which has a wind gradient.

Consider now what happens when a *heavy* ball is rolled across the platforms. As soon as it rolls onto platform 1 it finds the platform coming towards it at a speed of 5 ft./sec. (on account of its inertia it is not immediately carried along by the platform), or, what is the same thing, its speed has been increased in the direction opposite to the motion of the platform by this same amount. If it rolls across the platforms at the rate of 3 ft./sec. we can say that the ball receives an acceleration relatively to the platform, where it is at any instant, of 5 ft./sec.^{2}. This is the kind of quantity represented by (2). The direction of this acceleration is opposite to the motion of the platform.

Consider what would happen to yourself in stepping from one platform to the next one moving faster. Unless you especially prepared yourself you would fall sideways, your head pointing in the direction opposite to the motion of the platform. In other words, when you stepped across the line you received the equivalent of an impulse on your body directed up-platform since you fell with your head pointing in that direction. It is an impulse because the change in speed is sudden. If there were six platforms one-half foot wide instead of one 3 feet wide in every 3 feet, each moving 5/6 ft./sec. faster than the preceeding one, this impulse would become more nearly a uniformly acting force.

Now, as long as an airplane headed against the wind rises into wind of greater velocity it is acted upon by such a force and consequently flies at a greater speed than usual. The lift is increased and remains increased as long as the plane rises into faster moving air and the climb is improved.

On the other hand, converse phenomena take place when a body goes from a rapidly moving platform to a slower moving one. The accelerations are all reversed.

Besides the acceleration just described which acts on the plane, there is the acceleration of gravity. These two accelerations combine into one resultant of amount—

$$A = \sqrt{g^2 + \overline{aV \sin i}^2} \quad \ldots\ldots\ldots\ldots (3)$$

which makes an angle

$$b = \tan^{-1} \frac{aV \sin i}{g} \quad \ldots\ldots\ldots\ldots (4)$$

with the vertical
The plane flies relatively to this resultant acceleration A just as it flew previously in calm air with respect to the acceleration of gravity g.

If it can climb at an angle $i + 90$ with respect to the vertical (g), it can climb at this same angle (very approximately) with respect to A which to all intents and purposes becomes the new relative verticol.

Figures 4, 5, 6 and 7 show the direction of the resultant vector accelerations for a plane climbing up-wind; a plane climbing down-wind; a plane descending up-wind and a plane descending down-wind respectively—up-wind meaning flying against the wind, down-wind, flying with the wind.

Fig. 4. Climbing against the wind: The plane goes into faster moving air. The angle i is increased by the angle b, and the plane climbs better.

Fig. 5. Climbing with the wind: The plane goes into faster moving air. The angle i is diminshed by b and the plane does not climb so well.

Fig. 6. Descending against the wind: The plane goes into slower moving air. The angle i is increased by b and the plane descends at a steeper angle.

Fig. 7. Descending with the wind: The plane goes into slower moving air. The angle of descent i is decreased by b and the plane descends at a lesser angle.

Consider Cases 4 and 6. A pilot starts to climb, the plane is lively and climbs rapidly, the lift is increased. He starts to glide down, the plane descends rapidly, it has lost in lift and seems to fall.

Compare Cases 5 and 7. A pilot starts to climb; the plane acts sluggish and climbs badly, the lift is diminished. He starts

to descend, the plane tends to fly horizontally and he depresses the elevator in order to descend more rapidly.

Suppose now while descending he has spiraled and is now headed into the wind. Case 6 comes into effect and the pilot to his surprise descends at a perhaps alarming angle.

It must already be quite evident that the machine would seem to act queerly to a pilot unaware of the reasons for such behavior.

Effects to Be Expected on a Turn

Suppose that a plane flying horizontally up-wind makes a turn, either to the right or to the left, of 180° in order to fly down-wind. The turn produces a drop, hence the plane goes from horizontal flight up-wind, normal condition, into Case 7. The usual drop is minimized.

A plane flying horizontally down-wind, normal condition, makes a 180° turn in order to fly up-wind. A turn produces a drop, hence the plane goes from normal flight into Case 6. The usual drop is accentuated.

When the first 90° of a turn has taken place a corresponding drop has also taken place and the plane gets a sidewise acceleration which produces an effect similar to a side gust on a plane flying normally.

If originally flying up-wind, a 90° turn produces the equivalent of an up-wind gust.

If flying originally down-wind a 90° turn produces an up-wind gust.

Numerical Results

Referring to equation (4) defining b as the change in the angle i as small we can take this small angle to be the same as its tangent; the angle i is also small and no serious error is committed in using it directly instead of its sine.

Since then exactly

$$\tan b = \frac{a V \sin i}{g}$$

we can write approximately

$$b = \frac{a V i}{g}$$

and, therefore,

$$\frac{b}{i} = \frac{a V}{g}$$

which is the fractional change in climbing angle due to wind gradient a.

If a is in m.p.h. per 1000 ft.
V is in m.p.h.
and g is 32.2 $ft./sec.^2$, we may write this expression as

$$b/i = a\ V\ 0.0067\%$$

For example, if the wind increases at the rate of 20 m.p.h. per 1000 ft. and the plane is travelling at the rate of 100 m.p.h., the percentage change between climb up-wind and climb down-wind is a decrease of

$$2 \times 20 \times 100 \times .0067\% = 26.8\%$$

The difference in climb up-wind and climb in calm air for the same conditions is 13.4%. If the plane travels at 150 m.p.h. under the same conditions the percentage change becomes 20% instead of 13% and 40% instead of 26.8%. In other words, a certain fraction of the wind energy can be utilized in this manner.

If it be assumed that the wind has periodic increases and decreases in horizontal speed at any given level it is seen from the foregoing that by proper maneuvering its energy can be drawn on to partially sustain the machine. The great practical drawback, however, is that the pilot can only be aware of these changes by the "feel" of the plane and could only utilize them after long experience, if at all. Birds probably are instinctively able to adapt their flying attitude to these varying conditions and have the advantage also of the fact that small sized gusts can be utilized whereas with a large airplane it would require that the cross section of the disturbance be as large or larger than the airplane.

Forces and Moments Brought Into Play on Banking

There are still other actions taking place while making a turn in a wind in which there exists a wind gradient.

Consider an airplane flying against the wind which banks while making a 90° turn to fly across the wind.

Since the right hand wing rises and the left hand wing descends, the former is acted upon by an increased speed of down-wind and the lower by an increased speed of up-wind.



FIG. 8.

As seen in the diagram, this produces an upsetting couple FF' tending to increase the bank and sharpen the turn.

After the next turn of 90° to fly with the wind this couple disappears and two others make their appearance: one due to unequal drifts on the right and left wings, this drift being less on the higher and greater on the lower, which couple tends to yaw the machine slightly to the pilot's left, and the other due to unequal lift on the right and left wings, the lift on the upper being decreased and on the lower increased relatively. This couple tends to under bank the machine and is a righting couple.

Consider an airplane flying with the wind which banks while making a turn to fly across the wind.



FIG. 9.

This maneuver brings into existence a couple FF' tending to right the machine and widen the turn.

After the next turn of 90° to fly against the wind this couple ceases to exist and, as before, two new couples appear. One due to unequal drift tending to yaw the machine towards the pilot's right and the other due to unequal lift which is greater on the higher than on the lower wing, which is therefore an upsetting couple and tends to make the turn sharp.

The resultant effect as felt by the pilot is made up of these various separately described effects. There is, however, no question in our mind but that these effects produce the peculiarities felt by all pilots when maneuvering in the wind.

It should also be noticed that the relative value of these effects changes with the size and weight of the machine being flown.

Rough calculations were made of the magnitude of these couples for a machine of 40 ft. span, aspect ratio 6, weighing 3,000 pounds for a 20 m. p. h. per 1,000 ft. and an angle of bank of 45°.

The cross wind couple is negligible. The couple due to unequal lift gives a value of about 150 lb.-ft. The yawing couple due to unequal drift about 15 lb.-ft.

Bumps and Air Holes

The shocks which are nearly always felt in a machine in flight are somewhat of the same nature as the effect of un-

evenesses of a road on an automobile and are probably due to sudden small changes in wind speed or wind direction, or both.

As a slight change in vertical wind direction seriously modifies the lift it is easily understood that a sudden drop or rise will tend to take place, and as soon as the plane passes through the disturbance it regains the even tenor of its way.

The so-called holes in the air are easily explained as the result of the meeting by the plane of a fairly large area in which there is either: a sudden shifting of the vertical wind direction downward, producing not only a drop due to the downward component of the wind velocity, but also a decrease in lift due to the greatly decreased angle of incidence, the two combining into a sudden and alarming drop; or a sudden change in air temperature, this producing a corresponding change in air density and causing a sudden change in lift. This is a decrease if the temperature change is a rise. These two causes can also act simultaneously.

From the foregoing discussion it should now be realized that a thorough understanding by the pilot of the possible causes of peculiarities is absolutely necessary. This understanding is as necessary for the air pilot as it is for a car driver to know, for instance, that a car is liable to skid on a turn or that wet pavements are liable to be slippery. The knowledge of these causes gives him a realization of what is occurring and the reasons therefore, as well as indicating the proper maneuvers for overcoming their detrimental effects and utilizing them for his advantage.

Halford Aero Motor

The Auto Motor Repairing Co., of Brooklyn, announces the completion of the Halford Aero Motor, and gives the following brief particulars:

Standard Bore—

Ignition—Atwater-Kent;
Carburetor, Zenith;
Maximum speed, 1500 r.p.m.
Suited for a 6 ft. 6 in. propeller with 3 ft. pitch.

Special Bore—

Bosch magneto ignition;
Zenith carburetor;
Special oversized valves;
Forced feed lubrication;
Zepher pistons;
Special leak-proof piston rings;
Extra large carburetor;
R.P.M. up to 2000.
Suited for a propeller of 4 ft. to 5 ft. pitch.

The motor is a modified Ford motor which is expected to stand up well in aviation practice.



CAR OF THE U. S. NAVY O-1
(C) *International*

U. S. NAVY O-1, PURCHASED FROM THE ITALIAN GOVERNMENT
(C) *International*

Stine Screw Holes

Stine Screw Holes have been designed to meet a need that has long been felt in wood construction. They are made to fit all sizes of screws. After they are hammered in, the head is removed, leaving a permanent screw-hole. Besides this simplicity, whereby any one able to drive a nail is able to drive in a screw hole, it has also the qualities of neatness, durability and convenience.

The Stine Screw Hole is made of brass, and will therefore not rust under atmospheric conditions. Holes can be driven



without injury to the material, and in places where screws could not otherwise be used.

With special reference to the airplane construction, Stine Screw Holes may be useful in the following ways:

1. In the attachment of instruments to the instrument board.
2. In removable floor board and at points where removable seats are attached to the structural members of the fuselage.
3. For such control attachments as are necessary to dissemble when planes are taken down for shipping.
4. In securing removable sides of the costly cases in which planes are packed and shipped.

Development of a 15-Foot Airplane Wing Rib

By Raymond M. Wirka*

During the progress of the war the Forest Products Laboratory of the United States Forest Service, Madison, Wis., at the request of the Aircraft Division, Bureau of Construction and Repair, Navy Department, undertook the development of an airplane wing rib of minimum weight, having a chord length of 15 feet, and capable of sustaining, without rupture, a distributed load of 670 pounds.



FIG. 1.

Two distinct forms of rib were investigated at the laboratory as possibilities for development; namely, one having a plywood web, the other using some form of truss to carry the load. In the former type the web section was made of three-ply wood with adjacent plies glued at 90 degrees to each other; in the latter, various truss designs were tested.

Method of Test

Ribs for each design were tested under high-speed load distribution, and a few ribs of the final design were also tested under low-speed load distribution. The distribution diagrams shown in Fig. 2 were used.

Ordinates of both diagrams represent the sum of the unit lift pressures on the upper and lower wing surfaces. The apparatus used for applying load to the ribs is shown in Fig. 10. By dividing the bases of the diagrams (Fig. 2) into 16 equal distances and extending vertical lines upward, each diagram is



FIG. 2

divided into 16 areas. The 16 concentrated forces applied to the rib are proportional, respectively, to the 16 areas into which each diagram is divided. The downward motion of the movable head of the machine causes the load to be applied to the rib. To approximate the lateral stiffening the rib receives from the wing covering when in service in the airplane, the top and bottom flanges were fastened, by means of cords, to beams paralleling the rib and bolted to the testing machine.

Comparison of Ribs

All ribs tested were compared for total load sustained, weight, stiffness, and specific strength; that is, the ratio of the total load sustained in pounds to the weight of the rib in ounces. Another factor considered was adaptability to production. The values obtained from the different types of ribs tested are given in the tables of Figs. 11 and 12.

To determine the relative stiffness of the various types of ribs tested, the load sustained by the rib was plotted against the travel of the movable head of the testing machine. The stiffness of the rib is proportional to the load sustained at a



given deflection. Fig. 1 shows two typical load-travel curves, the upper curve being that of a Warren truss rib and the lower that of a twisted-veneer rib. The lower curve lacks stiffness at low loads probably because of initial slackness in the veneer tension members. The upper curve shows the effect of more rigid construction.

Besides stiffness, the curves show the total load sustained. The work necessary to cause failure can be determined by the integration of the area under the curve.

To obtain maximum efficiency from the wings when in flight it is considered desirable that the aerofoil change as little as possible. That is to say, other things being equal, the rib showing highest stiffness is the best.

Description of Ribs

Seven types of ribs involving 13 different designs were tested: plywood, wrapped veneer strap, twisted veneer strap, modified Navy design, Pratt truss, Warren truss, and double Pratt truss. A key to these various ribs is given in the following tabulation:

* Assistant Engineer in Forest Products, Forest Products Laboratory, U. S. Forest Service, Madison, Wis.

KEY TO FIGURES

Design No.	Type.	Strength Values, Weights, Dimension, etc. Fig. No.	Details of Construction. Fig. No.
..	Plywood circular opening.....	..	3
..	Plywood semi-truss	..	3
1	Wrapped veneer strap.....	11	..
2	Wrapped veneer strap.....	11	..
3	Wrapped veneer strap.....	11	9
4	Twisted veneer strap.....	11	5
5	Navy design (modified).....	11	6
6	Pratt truss	12	4
7	Warren truss	12	7-Part a
8	Warren truss	12	7-Part a
9	Warren truss	12	7-Part b
10	Double Pratt truss.....	12	8
11	Warren truss	12	7-Part b

Discussion of Results

Plywood Web Ribs.—In the development of ribs of chord lengths from 55 to 96 inches favorable results were obtained by using 3-ply wood webs having the face grain vertical and the core grain horizontal. The first of the 15-foot ribs to be tested was of this type, the faces of the plywood web being of 1/32-inch birch and the core of 1/16-inch Spanish cedar. Two types, the circular opening and semi-truss, Fig. 3, were used. These ribs failed by bending of the plywood between openings and by buckling of the web near the upper and lower cap strips.

An attempt was made to strengthen the rib for column action by glueing vertical battens to both sides of the web between openings, and to increase the resistance to buckling by gluing horizontal strips to both sides of the web near the upper and lower cap strips. The addition of this stiffening increased the weight of the rib considerably, without materially increasing the load sustained. Reinforced in this way the ribs weighed on the average about 2.5 pounds and sustained a load of about 250 pounds. These ribs were tested with the load distribution of Fig. 2-a.

While a plywood web rib could have been developed which would sustain the 670 pounds desired, previous tests on ribs of this kind indicated that such a rib would weigh considerably more than 3 pounds. The use of some form of built-up truss construction was therefore deemed necessary if a sufficiently light rib were to be obtained.

Wrapped Veneer Strap Rib.—In the wrapped veneer strap design, Nos. 1, 2 and 3, Fig. 11, an attempt was made to utilize the full tensile strength of the veneer tension members which extend the length of the rib and are wrapped as shown in Fig. 9. By the addition of channels in design Nos. 2 and 3 satisfactory strength was obtained, although the strength weight ratio was below that of some of the other types tested.

Twisted Veneer Strap Rib.—The twisted veneer strap ribs, No. 4, Fig. 5, failed repeatedly in the tension members at the lower cap strips near the front and rear spars. Better steaming of the diagonals before bending would probably have improved the strength somewhat although it is doubtful whether or not the strength values would have equalled those of other ribs tested. This rib was, further, not so stiff as some of the other ribs tested.

Modified Navy Design Rib.—Design No. 5 designated as the Navy design (modified) gave very satisfactory values of strength, weight, and specific strength, but required considerably more time in construction than some of the other ribs having equally good strength and weight values.

Pratt Truss Rib.—From previous tests on commercial 10-foot wing ribs of the Pratt truss type it was found that the strength of the joint between the diagonals and the cap pieces was almost wholly dependent upon the glue, the screws contributing



little to the strength of the joint. Because of failure in the glue the full tensile strength of the diagonals was not obtained. All diagonals of ribs of design No. 6, Fig. 12, were made of single-ply veneer to increase the area of the glued surface between diagonals and web strips. The strength and weight values of these ribs were very satisfactory and the ribs are very simple to construct.

Double Pratt Truss Rib.—The double Pratt truss ribs, design No. 10, are somewhat similar to those of design No. 6, and are suitable for reverse loading. The results obtained from tests on these ribs were not so satisfactory as those on ribs of the Pratt truss.

Warren Truss Rib.—Of the various designs of Warren truss ribs, design No. 11 proved to be the most satisfactory. All component members were made of spruce. The ribs are suitable for reverse loading, assuming the same load distribution.



FIG. 10. METHOD OF TESTING 15 FOOT WING RIBS FOR STRENGTH

Conclusions

The load-travel curves of the plywood web, twisted veneer strap, and Pratt truss types showed that ribs of of these types were not quite as stiff as those of the other types.

Although plywood proved very satisfactory for webs of ribs of short chord lengths, the development of 15-foot wing ribs has shown quite conclusively that a plywood web construction is impractical for ribs of this length.

Ribs of the Warren truss type, design No. 11, were superior in strength per unit weight to all other ribs tested. These ribs are partially dependent on glued surfaces for strength, they possess considerable residual strength due to the lapped and taped construction. Should failure occur because of poor gluing, however, they embody many of the desirable features of airplane wing ribs—high strength per unit weight, stiffness and simplicity of design—and possess, in addition, considerable strength in reverse loading.



STRENGTH TESTS ON 15 FOOT AIRPLANE WING RIBS

PROJECT L-225-2

DESIGN NO.	TYPE	LOAD DISTRIBUTION	NO OF TESTS	W = AK WEIGHT OF RIBS LB.	P AK TOTAL LOAD SUSTAINED LB.	RATIO P/W W = AK WT OF RIBS OZ.
1	WRAPPED VENEER STRAP	FIG. 2	3	2.70	496	11.5
2	" " "	"	2	3.60	772	13.4
3	" " "	"	2	3.45	854	15.5
4	TWISTED VENEER STRAP	"	3	3.16	447	8.8
5	NAVY DESIGN (HOOFIELD)	"	3	2.51	729	18.2

CONSTRUCTION OF RIBS

DESIGN NO.1 - 1/30" x 1 3/4" birch veneer continuous web tension members. 7/16" x 1/2" spruce cap strips, one side rounded. 3/16" x 3/8" spruce compression members.

DESIGN NO.2 - Same as design NO.1 except cap strips reinforced with spruce channels 7/8" x 3/4" outside, 3/8" x 3/8" inside.

DESIGN NO.3 - 1/30" x 1 3/4" birch veneer continuous web tension members. Half-round spruce cap strips 3/16 diameter reinforced with spruce channels 13/16" x 11/16" outside, 1/2" x 3/32 inside. 3/8" x 3/8" spruce vertical compression members.

DESIGN NO.4 - 1/8" x 3/4" and 1/16" x 3/4" birch veneer continuous web tension members. Spruce channel cap strips 11/16" x 7/16" outside, 11/16" x 3/4" inside. 3/16" x 3/8" spruce compression members.

DESIGN NO.5 - 3/16" x 3/8" oak continuous web members. T-section spruce cap strips. Joints wrapped with linen cord and doped. 3/8" x 3/8" spruce vertical members.

FOREST PRODUCTS LAB
FOREST SERVICE
U.S. DEPT OF AGRICULTURE
MADISON, WIS.

FIG. 11



STRENGTH TESTS ON 15 FOOT AIRPLANE WING RIBS

PROJECT L-225-2

DESIGN NO.	TYPE	LOAD DISTRIBUTION	NO. OF TESTS	W = AK WT. OF RIBS LB.	P AK TOTAL LOAD SUSTAINED LB.	RATIO P/W W = AK WT. OF RIBS LB.
6	PRATT TRUSS	FIGURE 2	3	2.45	700	18.0
7	WARREN TRUSS	" "	3	3.63	850	14.5
8	" "	" "	3	2.97	748	15.7
9	" "	" "	3	2.90	849	18.3
10	DOUBLE PRATT TRUSS	" "	3	2.96	606	12.8
11	WARREN TRUSS	" "	3	2.83	742	20.6
11	" "	FIGURE 4	3	2.26	374	26.9

CONSTRUCTION OF RIBS

DESIGN NO.6 - 3/8" x 7/8" spruce cap strips. 3/16" x 3/4" spruce web. 7/16" x 7/16" spruce compression members. 1/30" birch veneer tension members. Joints glued and nailed.

DESIGN NO.7 - Spruce channel cap strips 7/8" x 3/4" outside, 3/4" x 1/2" inside. Web members 1/2" x 1/2" 7-plywood (2 plies birch faces, 5 plies yellow poplar core) Joints glued riveted, wrapped with linen, and doped.

DESIGN NO.8 - Same cap strips as in design no 7. Vertical members and 10 diagonal members between spar openings, 3-plywood (2 plies birch, 3 plies basswood). All other diagonal members Spruce. Joints glued, riveted, wrapped with linen, and doped.

DESIGN NO.9 - Same cap strips as in design no.7. All vertical members and diagonal members next to front and rear spar openings in center section 2:1 Spruce. All other diagonal members 3/8" x 1/2" spruce Joints glued, wrapped with linen and doped.

DESIGN NO.10 - Spruce channel cap strips 7/8" x 11/16" outside, 11/16" x 1/2" inside. 3/8" x 1/2" Spruce compression members. 7/16" x 1 1/4" basswood tension members. All tension members in pairs. Joints glued and tacked with 3 tacks

DESIGN NO.11 - Spruce channel cap strips 3/8" x 1/2" outside, 7/16" x 7/16" inside. All diagonal members 3/64 1/16 Spruce, except those on each side of front spar opening 1/2" x 1/16" Spruce. Vertical members 3/16" x 7/16" Spruce. Joints glued, nailed, wrapped with linen and doped.

FOREST PRODUCTS LAB
FOREST SERVICE
U.S. DEPT OF AGRICULTURE

FIG. 12

Note on the Effect of Water Vapor in Hydrogen Upon the Lifting Power of the Gas

In conection with the discussion of the purity of hydrogen it is interesting to note the effect of water vapor upon the lifting power of hydrogen. The specific gravities of hydrogen and water vapor are 0.0695 and 0.622. The reduction in lifting power of hydrogen when saturated with water vapor at different temperatures is shown by Fig. 1.

If hydrogen is compressed in cylinders and the cylinders contain some water in the liquid form, then the hydrogen will be saturated with water vapor at the temperature of the cylinder and each volume of the high-pressure hydrogen will contain the same volume of water vapor as it would if under a pressure of one atmosphere and at the same temperature; hence when it is withdrawn from the cylinder and expanded to the lower pressure it contains only a relatively small amount of water vapor per unit volume. The gas is, therefore, comparatively dry if it has been expanded from a high pressure. The magnitude of the loss in lifting power at one temperature (30° C.) and different pressures is shown in Fig. 2. The data in Fig. 2 are computed on the assumption that the gas will be expanded from the high pressure to atmospheric pressure without either mechanical entrainment of liquid water that may be in the high-pressure container or absorption of water vapor from this liquid during the period of expansion of the gas.

In considering the advantages of using dry hydrogen for inflating balloons the fact should not be overlooked that rubberized balloon fabrics are somewhat permeable to water vapor. Therefore, even though the gas is put into the balloon dry it will become partially saturated with water vapor which penetrates the fabric and will ultimately approximate the moisture condition of the surrounding atmosphere.



FIG. 1. TEMPERATURE



FIG. 2. GAGE PRESSURE—POUNDS

The Static Head Turn Indicator for Airplanes*

By Sir Horace Darwin, K.B.E., F.R.S.

An instrument to indicate whether, under all conditions, the path of the airplane is a straight line or whether it is turning to the right or left is much required. It is well known that when flying in a cloud or at night, and no fixed object is visible, even the most experienced pilot may, without realizing it, be flying on a sharp curve. If, however, the angle of banking is great the muscular reaction of his body will have to be increased to counteract the increased force acting on it. This will tell him that his course is not straight, but there is nothing to show whether he is on a right-hand or left-hand turn. If he tries to straighten his course he is just as likely to increase the curvature as to straighten out. If he observes his compass he will probably find that it is swinging so much that it will tell him something is wrong, but give no guide to what he should do.

A turn indicator enables a straight compass course to be kept when flying in clouds or at night, and this is valuable for long-distance flights. But straight flying is always important. If the clouds are low and the airplane leaves their lower surface when on a sharp turn there may not be sufficient time to allow the machine to be put into a safe position for landing before the ground is reached.

Successful turn indicators using gyroscopes have been made.

With the static head turn indicator, in conjunction with a good airplane compass and a cross level, a true compass course can be kept in clouds or at night. The success of this instrument is due to the large amount of experimental work done at Orfordness and at the Royal Aircraft Establishment, and to the design of the Ogilvie pressure gauge manufactured by the British Wright Co. Unless a pressure gauge as good and as sensitive as this instrument had been designed, the turn indicator would not have been a success.

A great number of experiments had to be tried in order to determine the best position for fixing the static heads, on the relative advantages of fixed and swivelling static heads, and on the effect of side-slip.

A sensitive differential manometer is fixed on the instrument board, and the Ogilvie pressure gauge is used for this purpose. The two openings from it are connected to two static heads, fixed to the wings as far apart as can conveniently be arranged, and in a position so that the air pressure at these points is influenced as little as possible by the wings or body of the airplane. The manometer will then indicate a difference of pressure when the airplane is turning. The hand will move in one direction for a turn to the right and in the other direction for a turn to the left.

The pressure gauge was designed by the British Wright Co. for use with the turn indicator, and is of the Ogilvie type. An extremely sensitive circular rubber diaphragm separates two chambers in the instrument. These chambers are connected, one to each static head, and the minute difference of pressures caused by the airplane turning deflects the diaphragm by a small amount. The deflection is communicated directly by a silk thread, without intermediate gear, to the indicating hand and moves it to the right or the left. The scale carrying the zero mark and divisions is adjustable by the pilot during flight by the use of one thumb, and he can easily set the scale in the correct position when flying on a straight course immediately after leaving the ground. This adjustment is most desirable, as it is found that the position of the hand when on a straight course does not correspond with absolute equality of pressure on the two sides of the diaphragm.

This is due both because it is impossible to make both static heads absolutely similar, and also because the actual static pressure at the two positions where the static heads are fixed are not equal. No doubt if it were possible to fix the static heads at a great distance in front of the wings the amount of adjustment required would be greatly reduced. The adjustment required is seldom more than 10 deg.

The air inside the static openings is very nearly the true air pressure outside in a well-designed static opening. The static heads used are the same in form as those used in the standard air-speed indicator. The tube moves through the air in the direction of its axis; the stream-line end of the tube disturbs the air as little as possible, and thus the air passes over the holes in the side of the tube at right angles to their direction. It had been found by experiment that the air pressure inside the tube is very nearly the true pressure outside, whatever the velocity the tube moves through the air may be.

A great authority on birds tells me that he has no doubt that birds breathe through their nostrils. He might find it difficult to actually prove this, but it is very unlikely that he is not correct. It is an interesting fact that the nostrils of birds fulfil to some extent the conditions of a well-designed static opening; the nostrils are holes in the beak, and in flight the beak moves through the air point forwards. It is clear that this arrangement is advantageous to the bird. To ensure ease in breathing, the air inside the lungs should be at the same pressure as the air outside. I do not know whether men in airplanes find any difficulty in breathing when the head is in the wind. If they do, no doubt the difficulty could be reduced by breathing through properly constructed static openings.

Experiments were tried with fixed static heads, as it was hoped that the swivelling form was not necessary. They were fixed to the struts between the wings, but in this position side-slipping had a considerable effect; in some cases this was so great that the index of the pressure gauge showed a right-hand turn when a left-hand turn was taken. The fixed static heads were then placed in front and above the leading edge of the upper wing. In this position the results were much better, but the heads must be truly parallel. In this exposed position it was found that they were liable to become accidentally displaced, and as this might easily happen without the pilot knowing it, then the instrument would not be trustworthy. When swivelling heads are used and placed in the standard position the effect of side-slip is greatly reduced and turns to the right or left are correctly indicated. To eliminate all effect of side-slip the static heads must be put inconveniently far from the wings.

The swivelling static heads are required to adjust their angle with the greatest freedom. They are carried by swivelling bearings allowing universal movement and fixed to rigid standards. The air is always free to flow by way of a rubber tube, which twists to accommodate the adjustment of the head to right and left and bends to permit of inclination up and down. The static head, thus free to move in all directions, is maintained parallel to the direction of the wind by means of a conical vane. Its weight has no tendency to move it out of the true direction, as it is carefully balanced about its swivelling bearings.

It was also found important to avoid sharp bends or constrictions in the tube, as otherwise the indication on the dial was sluggish. The air tube on the static head openings becoming blocked with ice is a possible cause of failure.

In order to make the action clear, we will assume that the airplane is moving in a circle, that it is not banked, and that the air tube connecting the static heads is horizontal and points along a radius of the circle. The forces acting on the air in this tube are:

1. Gravity acting vertically downwards. As the tube is horizontal, this will cause no difference of pressure at the manometer or cause any tendency of the air to move along the tube.

2. The atmospheric pressure at the static heads. As the tube is horizontal the pressures at the ends of the tube are equal and in opposite directions, and no effect is produced on the manometer.

3. The pressure of the inner surface of the tube against the air; this clearly has no effect on the manometer.

4. Centrifugal force is the one remaining force which can cause a movement of the differential manometer. The air will tend to move along the tube in an outward direction and can

* Abstract of paper read before the Royal Aeronautical Society at the Royal Society of Arts on Wednesday, Oct. 29, 1919.

only be prevented from so doing by a difference of pressure on the two sides of the diaphragms in the manometer. It is this difference of pressure which is indicated on the manometer and shows a right or left-hand turn.

All turns, however, are banked, and this assumption is only made to make the action clear.

Let us now consider a banked turn and assume that the aeroplane is banked at the correct angle. By the correct angle is meant an angle which causes no side-slip; that is, such an angle that the apparent direction of gravity (that is the resultant of gravity and centrifugal force) is at right angles to the plane of the wings.

Again consider the forces acting on the air in the tube.

1. As the banking is at the correct angle, the resultant of gravity and centrifugal force act at right angles to the direction of the tube and have no effect.

2. The pressure against the inside of the tube clearly has no effect.

3. The atmospheric pressure at the two static heads is not equal; as the airplane is banked, the outer end is higher up and at a place where the air is at a less pressure. The differential manometer will show this difference of pressure.

Or we can consider this last case differently. The forces acting on the air in the tube are:

1. Gravity acting on the air in the tube. As the tube is banked, this will tend to make the air flow inwards.

2. Atmospheric pressure at the static heads. As the pressure at the outer end is less than at the inner end, these pressures will tend to make the air flow outwards. The tendency of (1) and (2) are obviously equal and in opposite directions, and the combination of the two will have no effect.

3. The pressure against the inside of the tube clearly has no effect.

4. Centrifugal force is the only remaining force, and this clearly will cause a difference of pressure on the two sides of the diaphragm of the manometer. Although these two ways of considering the forces which act on the air in the tube are so different they are both correct.

If V = the speed of the aeroplane.
r = radius of the circle in which it is flying.
b = the distance between the static heads.
ρ = the density of the air.
P = the differential pressure on the air required to prevent its movement along the air tube.
β = the angle of banking.

With horizontal flight, no side-slip and the air tube in the vertical plane passing through the centre of the circle

$P = v^2 \rho b \cos \beta / r$.

Usually β is the correct banking angle, then $\tan B = v^2 g r$: In order to make P large, b must be large. As the density of the air becomes less with increased height the indications will also become less.

The instrument can only be used for measuring r if we know the speed and the density of the air, but it is not wanted for this, and is only useful for showing that the airplane is turning to the right or the left.

If an airplane is flying near the ground at 80 m.p.h. in a circle of one mile radius, a complete circle would be flown in 4½ mins., and the correct banking angle would be 4°—40'. If the static heads are 30 ft. apart the air pressure in the manometer would be about 1 mm. head of water when flying near the ground. This pressure will move the head on the dial through about 14 deg. or about 1½ divisions, and the turn will be clearly shown. If the height of the airplane is so great that the density of the air is reduced to half its normal amount the indication will also be reduced to one-half.

The turn indicator has been tried on many different types of airplanes. The following are some extracts from a report which we have been kindly allowed to see and quote:

"In connection with the daily cloud and horizon observations, it has been necessary to attempt to fly through thick layers of cloud. This has been tried on several types of scouts and after considerable practice it was found possible to get through several thousand feet of solid cloud, but it required very rigid concentration on the control of the machine, even then it frequently got out of control and after losing height, climbing had to begin again. It was practically impossible to have any sense of direction during a long climb in cloud. Layers of cloud of various thicknesses up to 6,000 ft. were got through, but it was decidedly unpleasant flying."

The turn indicator was then fixed to a 110-h. p Le Rhone Camel, a difficult scout to fly through clouds. The first position of the static heads was not found satisfactory. A second position was tried. The report goes on:

"Although not extremely sensitive, it was most useful, enabling the machine to be flown in comfort for a considerable time in clouds. . . . As compared with the experience in clouds on scouts without turn indicators, flying in clouds was now quite pleasant, as the machine never showed any sign of getting out of control. To fly straight was quite easy, keeping a fairly reasonable compass course, to make a gentle spiral up or down, or a very steep spiral. . . .

"The static heads were only tried in two positions, but it may be that a position could be found without their being unreasonably far in front of the plane, so that the indicator would be more sensitive.

"It would need some considerable practice before the average pilot could take a Camel or most scouts through much cloud, but it makes cloud flying on scouts possible, whereas without turn indicators it is practically impossible."



JUNKER FIREPROOF ALL METAL PASSENGER AIRPLANE. THIS MONOPLANE IS REPORTED TO HAVE A SPEED OF 110 M.P.H. ANOTHER VIEW OF THIS MACHINE WAS SHOWN IN THE LAST ISSUE

(C) *Wide World Photos*

The Linke-Hoffman Central Power Plant Giant Biplanes

By Eric Hildesheim

Some detailed information is now available of the giant airplanes built by the German Linke-Hoffman works, embodying a central multiple engine power plant with a single or twin tractors.

The LHR1

It appears that the first Linke-Hoffman model (LHRI), shown in Fig. 1, was of an unsuccessful character. The



FIG. 1. REAR VIEW FIRST EXPERIMENTAL LINKE-HOFFMAN

typical Roland contruction was followed here in the design of a body occupying the entire gap from wing to wing. Experiments in the Göttingen wind tunnel indicated increase of aerodynamic efficiency, but in practice the lateral control proved very slow, and pilots could not seemingly judge landing distances in the totally enclosed body. A good point



FIG. 2. FRONT COCKPIT SHOWING TRANSPARENT ROOF

in the design of the machine was the mounting of the tractor screws independently of the wing structure. Most accidents experienced with the Zeppelin-Staaken, with engine mounting supported by the wings, were due to stripping of gears,



FIGS. 3-4. REAR VIEW OF LINKE-HOFFMAN R-2

and failure of engine mountings, leading to destruction of the wings themselves.

Figure 2 shows a good view of the front cockpit in the nose of the enclosed fuselage of the LHR1 and the transparent roof is clearly indicated.

The LHR2

In the LHR2, which was decidedly more successful than the LHR1, there were a number of important modifications. Fig. 3 indicates how closely this later model resembles an ordinary biplane in its general lines, and Fig. 4 gives an excellent rear view of this machine. It is interesting to com-



FIG. 5. ENGINE VENTS, EXHAUST PIPES, RADIATOR

pare the main dimensions and the performance of the two models:

	LHR1	LHR2
Span	33.2 metres	42.1 metres
Overall length	15.6 metres	20.3 metres
Height	6.7 metres	7.1 metres
Total wing area	265 sq. metres	320 sq. metres
Power Plant	4-260 HP Mercedes	4-260 HP Mercedes
Weight Empty	8 tons	8 tons
Useful load (including fuel)	3.2 tons	4 tons
Total load	11.2 tons	12 tons
Maximum speed	130 kilometres pr. h.	130 kilometres pr. hr.
Climb	3000 metres in 2 hrs.	3000 metres in 2 hrs.

While the LHR2 retained the power plant and trans-



FIG. 6. SPIRAL SPRING SHOCK ABSORBERS

mission system of the LHR1, it embodied many new ideas, the outstanding feature being the use of a single tractor screw and the general resemblance to an ordinary tractor biplane.

Even the two-wheeled landing gear of Fig. 6 is nothing but an enlarged edition of ordinary airplane practice. It is claimed and not without likelihood, that the large size of the wheels enables them to pass over ditches without danger of the aircraft overturning. A winter test is quoted by the Germans, when to avoid landing in snow on the aerodrome the plane passed on to a neighboring marsh, where two ditches were passed without overturning, the plane finally coming to rest with the wheels embedded 12 in. in the marsh. Fig. 6 shows the very logical provision of the side shock absorber. The straits to which the Germans were driven for lack of



FIG. 7. ENGINE AND GRAVITY TANK MOUNTING



FIG. 8. ENGINE ARRANGEMENT, SHOWING GEARS AND CLUTCH

material is indicated by the use of steel spiral springs in lieu of rubber shock absorbers, and by the use of wooden tires.

It will be noted that the somewhat peculiar construction of the tail surfaces of the LHR1, with a monoplane stabilizer and double elevator, has been replaced by the biplane stabilizer and elevator in the LHR2.

The rear part of the fuselage has a transparent covering to enable ready inspection of controls.

Little information is available regarding the transmission between the four engine unit and the single screw. Apparently the various engines transmit their power to one central shaft, carrying a single transmission gear wheel as shown in Fig. 9.

Figure 10 shows the commodious pilot's cockpit with dual control, looking into the engine room.

At a speed of 120 kilometres there is a fuel capacity of 30 hours with a load of 2 pilots, mechanics and navigators with their luggage and necessary instruments. For com-



FIG. 9. SINGLE GEAR WHEEL OF THE FOUR ENGINES

mercial aviation the Linke-Hoffman R2 model is now provided with an enclosed cabin for 12 passengers aft of the pilot's cockpit.

Various advantages are claimed for the central power plant installation as compared with the interplane power plant installation, such as the absence of side obstructions

for vision and gun range; the decrease in number of mechanics, since one mechanic can now take care of all four motors, a more complete understanding between engineers and pilots. The central power plant with single screw has a further advantage in simplicity over the twin screw type, and the few parts can be made rugged. The slow turning propeller can be made very efficient. There is almost complete reliability in the power system.



FIG. 10. PILOT'S COCK PIT LOOKING INTO ENGINE ROOM

Book Review

HOW AN AEROPLANE IS BUILT, by Stepney Blakeney. 233 pages. Aeroplane and General Publishing Co.: London. 5/— net.

This book appeared originally as a series of articles in the *Aeroplane*. Mr. Grey, the writer of the introduction, states that Mr. Baker has an intimate knowledge of detail work. We can thoroughly endorse this opinion.

At first it might be thought that this was merely a descriptive book on the building of small airplane models, but as a matter of fact, it is a thoroughly practical and most comprehensive manual of airplane construction. We might almost say it is the first work of its kind in the airplane field.

The author describes the most practical way of building longerons, struts, spars, gives detail instructions as to jigs, assembly, erecting and setting out. The text is illustrated with the best kind of sketches.

Wing covering and doping are treated somewhat sketchily but this is more than made up for by the careful remarks on metal parts and fittings.

A great many of the practical tips which it takes an airplane man years to learn are to be found in this little book.

Resume of Wind Tunnel Tests of Airship Envelopes

By J. C. Hunsaker, Eng. D.

A large number of stream-line bodies have been tested in the 8-ft. wind tunnel of the Washington Navy Yard, and without going into the details of these tests certain conclusions of general interest have been reached.

The resistance in a relative wind of velocity V is expressed by the formula

$$R = C\, C/g\ (\text{Volume})^{2/3}\, V^2$$

when C/g is the density of the air and C a coefficient and nearly constant. The form having the lowest value of the coefficient C has the least resistance for given volume or buoyancy. This expression was first proposed by Prandtl and is in general use.

In the course of tests on various forms, the coefficient C has been found to vary with the speed of the wind or as the quantity VL as would be expected from dimensional theory. The resistance can only vary as V^2 when the resistance is caused by eddy making. Good stream-line forms have a minimum of eddy making resistance and skin friction has a relatively large effect.

In fact, for seven models of very different shapes, representing seven actual dirigibles, the skin friction computed by Zahm's formula, $.00000778L^{.93}V^{1.86}b$, amounts to from 79 to 73 per cent of the total resistance observed.

The coefficient C appears to vary between $V^{-.12}$ to $V^{-.42}$.

The disk ratio or ratio of total resistance of model to its major circle varies between 15 and 17.

The resistance as measured appears to vary not as V^2, but by a lower power. Individual models show exponents between 1.85 to 1.92.

Yawing moments determined for several models indicates practically no differences for small angles. It appears to be immaterial what form of bow or stern is used within reasonable limits.

The shape of the mid section has the most important effect on resistance. Bow and stern are less important. A parallel middle body is disadvantageous, and for a length added equal to diameter may increase resistance 15 per cent.

The form of bow is slightly more important than the stern. A pointed nose can be replaced by a rounded one of good shape without change in resistance. A long, fine or conical tail is much worse than a shorter, rounded one of easy curvature. A fineness ration between 5 and 6 appears more advantageous.

The above notes apply only to good forms. The forms tested vary in resistance, depending on shape, not more than 8 per cent above or below the average of the series.

HYDRO BOAT INVENTED BY ALEXANDER GRAHAM BELL REPORTED TO MAKE 71 MILES PER HOUR. LIBERTY ENGINES
(C) *International*


HISPANO-
SUIZA
Aeronautical
Engines
Manufactured by
Wright-Martin
Aircraft Corporation
New Brunswick, N. J.
LOWER HALF CRANKCASE
STUD ASSEMBLY

MAYNARD LOSES R
TO DONALDSON

TWO RECORDS ESTABLISHED DE

Captain Averages 108 Miles an Hour; Covered 823 Miles in Day. Ca

Although Lieut. Belvin W. Maynard, the "flying parson," was the first aviator to fly from Mineola to California and return in the transcontinental aerial derby, an unofficial calculation of his flying time and that of other aviators eliminates him from first placee in the race.

It is estimated that Capt. J. O. Donaldson, second to return to Mineola, and the aviator who made the flight in an SE-5, a one man scout plane equipped with a 150 horsepower American built Hispano-Suiza motor, travelled twice across the country, a distance of 5,400 miles, in 49 hours, 56 minutes and 11 seconds. Lieut. Maynard's unofficial time in the air was 50 hours, 13 minutes and 34 seconds. In reckoning his time, however, there must be added a period of eighteen hours in which he was on the ground between control stations changing his motor.

Capt. Donaldson, a veteran flier of the war, * * * * * * * * * * is credited with two world's records established in the flight: One for covering the 5,400 miles at an average speed of 108 miles an hour, and the other for making a single day's flight of 823 miles, accomplished last Saturday when he flew from Rock Island, Ill., to Binghamton, N. Y.

Engine Works Like Clock.

Besides these records Capt. Donaldson also has the distinction of being the only aviator to make the flight with the same motor, which was still in perfect working condition at the finish. The engine worked like a clock at all times, and it was not even necessary to change a spark plug. * *

EVENING SUN N.Y.
OCT. 22ND 1919

Air Fans for Driving Generators on Airplanes

By Capt. G. Francis Gray, U. S. A.; Lt. John W. Reed, U. S. A., and P. N. Elderkin

Engineering and Research Division, Radio Development Section, War Department, Washington, D. C.

In this paper the authors first briefly describe the method employed by the Radio Development Section of the War Department in testing air fans used for driving the electric generators usually installed on airplanes for radio communication. They next discuss at some length the various types of air fans used during the war and present numerous photographs and curves clearly illustrating the construction of the fans and their operating characteristics.

The difficulty of the problem lay in designing a fan which would turn at constant speed in the air streams of widely varying speed set up by the airplane in flight. The various types of fans tested were: Fixed-blade fans of special blade shape; fixed-blade fans with wind brakes centrifugally regulated; fixed-blade fans using a friction clutch or a friction brake centrifugally regulated, and pivoted-blade fans in which the pitch is centrifugally regulated.

During the war extensive use was made of radio telegraph and telephone apparatus on military airplanes, and the problem of power supply for such equipment received a great deal of attention. The possible sources of energy may be listed as follows:

a Storage batteries or dry batteries.

b Generators driven from the airplane engine, with or without floating storage batteries, and supplying the radio sets directly or through dynamotors.

c Generators driven by separate gasoline engines.

d Generators driven by air fans or "windmills" placed in the air stream outside the airplane fuselage.

From an economical point of view, method *b* is preferable. It was seriously considered, but since it involved cooperation between organizations normally operating independently its adoption was delayed. Meanwhile the practice in our army followed that of our Allies, principally the French, in the use of method *d*, mounting the generator outside the airplane fuselage and driving it with an air fan.

The work done on the development of air fans for this service was carried out by the Radio Development Section of the Signal Corps, and since it was done under the press of military necessity it was directed entirely by utilitarian considerations, was often fragmentary, and neglected investigations, the need of which was realized but for which time and personnel were not available. This record is presented with the work still in unfinished form in the hope that results obtained may be useful to those who may have occasion to carry out further investigations on the problem.

Conditions for Which the Air Fans Were Designed

Two sizes of generators were to be driven by the air fans it was desired to develop. The essential data on these are as follows:

	Generator for Radio Telegraph Sets.	Generator for Radio Telephone Sets.
Generator diameter, in	6¼	4 15/16
Generator output, watts	200	80
Required power from fan, watts	330	250
Normal speed, r.p.m.	4500	4000

Methods of Test

Practically all of the tests recorded in this paper were made with the wind tunnel of the Bureau of Standards, and the management and personnel of the Bureau aided materially in expediting them. A special testing generator was mounted in the wind tunnel and the fan to be tested was attached to it. This generator was provided with a magnetic tachometer, a separately excited field, and convenient means for applying load to the armature circuit. The external shape and size of the machine were made identical with those of the radio generators, with which the air fans were to operate in service, and with this generator and the regular wind-tunnel equipment for measuring wind velocity, tests could be made rapidly and accurately.

All of the air fans considered in this development have normal speeds of 4,000 r.p.m., or above, and the centrifugal forces are very considerable. It was therefore found necessary to provide an overspeed test to precede the wind tunnel test. For this purpose a 30-hp. motor operating through a 43-to-3 De Laval speed-increasing gear to a suitable shaft extension for the fan was set up. This device was capable of driving the air fans at speeds up to 14,000 r.p.m., and to prevent damage to gears or bearings in case of failure of the fan a "weakest point" was provided by a replaceable notched shaft extension. Failure at this point merely resulted in the breaking of the replaceable shaft extension and of course the destruction of the fan, without injury to bearings or gears. Heavy guards prevented the flying fragments from causing any damage. This equipment was designed by Capt. F. E. Pernot, Officer in Charge of the Signal Corps Laboratories at the Bureau of Standards. There is one serious objection, however, to this method of over-speed testing in that it absorbs a large amount of power and puts abnormal thrust strains on the fans. A baffle to prevent air flow materially reduced this effect and later experience indicated that it would have been preferable to make the overspeed test in a very simple auxiliary wind tunnel with an aperture just large enough to drive the unloaded fans at the speed desired. Nevertheless, the apparatus just described was used in all tests discussed in this paper.



FIG. 1. PRE-WAR AIR FANS

In cases where the strength of a fan was problematical it was first given an overspeed test only slightly in excess of the running speed expected in the wind tunnel. After the wind-tunnel test it was again tested to the required overspeed or to destruction. The best fans were required to withstand up to practically double normal speed.

Simple Non-Regulating Air Fans

As in all power plant problems, the ideal in this development was a constant-speed drive for the radio generator. When the development began the only air fans available were non-regulating wooden fans such as those illustrated in Fig. 1. These fans have the characteristic that rotational speed is practically proportional to air speed, and when combined with the normal variations in the speed of the airplanes this fact leads to very severe requirements for the generator. As an example, a generator which would give satisfactory performance at 3,750 r.p.m. was required to withstand an overspeed test of 14,000 r.p.m. for mechanical performance and, with the addition of a very special regulating device, to hold

By courtesy of the American Society of Mechanical Engineers.

its voltage within 15 per cent at speeds from 4,000 to 12,000 r.p.m.

Although the need for better air fans was obvious, the non-regulating types had to be used until others could be developed, and a considerable amount of work was done in adapting them to the particular requirements to be met. Fig. 2 shows the construction of one of the final forms used with



FIG. 2. TYPE FA-3, NON-REGULATING AIR FAN, FOR RADIO-TELEPHONE GENERATORS

generators for radio-telephone sets, and Fig. 3 its performance in the wind tunnel. Figs. 4 and 5 give similar information on a larger size fixed-blade fan used for radio-telegraph sets. Fig. 5 also gives an idea of the variation in individual fans supposed to be identical. Considerable trouble was experienced with these fans, due to the fact that the method for calculating air fans was assumed to be the same as that used for propellers.

Obviously it is desirable to establish the correct method of calculating these fans, but the pressure of more important work prevented its being undertaken by the Radio Development Section. The subject, however, was given much attention by Mr. E. N. Fales, of the Airplane Engineering Department, Bureau of Aircraft Production of the Army, who



FIG. 3. PERFORMANCE CURVES OF TYPE FA-3 AIR FAN
(Diam., 15 in.; pitch, 2.1 ft.)

assisted the Section very materially during the early stages of the development described in this paper, and it is hoped he will publish his conclusions.

Regulating Air Fans

No one can work with simple air fans without being impressed with the desirability and apparent simplicity of modifying them so that instead of the straight-line relation between air speed and speed of rotation there will be more or less tendency toward constant rotational speed with varying air speed. Among the disadvantages which may be corrected by making the air fans self-regulating are the following:

a Undue head resistance.
b Excessive centrifugal stress in armature windings.
c Vibration.
d Commutator and bearing troubles.
e Troubles with voltage regulators.
f Troubles in radio sets due to varying voltage.

During the progress of this development a great many schemes for the construction of self-regulating fans were proposed. As all previous experiences led to the conclusion that the performance of a fan could not be predicted with any

FIG. 4. TYPE FA-6 NON-REGULATING AIR FAN FOR RADIO-TELEGRAPH GENERATORS

degree of accuracy, every reasonable suggestion was carefully considered and if possible tried out. Fundamentally all the fans tested may be classified under five principles of operations, as follows:

a Fixed-blade fans of special blade shape.
b Fixed-blade fans with wind brakes centrifugally regulated.
c Fixed-blade fans using a friction clutch centrifugally regulated.
d Fixed-blade fans using a friction blade centrifugally regulated.
e Pivoted-blade fans in which the pitch is centrifugally regulated.

Fixed-Blade Fans of Special Shape. Certain air fans submitted to the Signal Corps were supposed to give speed regulation on the principle that the angle of attack and efficiency can be made to alter with the wind velocity in such a way that the ratio of wind velocity to r.p.m. need not be constant. Tests were made first on a series of blade sections and later on a fan, shown at the right in Fig 1, which was said to possess the regulating features in a marked degree. The conclusion from these tests was that at no load the performance of properly designed fans tends to confirm the hopes of the designers, though the magnitude of the regulating effect is small; but under load, particularly varying load, it was impossible to distinguish any improvement over the ordinary fixed-blade types of fans. Consequently this method was discarded as of no practical value.



FIG. 5. PERFORMANCE CURVES OF TYPE FA-6 AIR FAN
(Diam., 20 in.; pitch, 1.75 ft.)

Fixed-Blade Fans with Wind Brakes. Fans of this type are

provided with wings, pins or other projections which are normally enclosed in a recess in the blade, but which are caused by centrifugal force to emerge and so retard the rotation of the fan. They have the disadvantage of low efficiency and consequent high head resistance, but were considered worth trying. Fig. 6 shows various development models.



FIG. 6. FIXED-BLADE FANS WITH WIND BRAKES

Round rods, rods with cloth and metal wings, flat strips, etc., were tried for the moving brake element. Many showed practically no regulation of course, but others were reasonably promising. Among such was the type in which the brake arms were pivoted and moved out into the air by the action of centrifugal weights. Another interesting fan had the break arms actuated not by centrifugal force, but by the air pressure on a plate mounted in advance of the nose of the fan, and gave a curve in which, for a certain range, the r.p.m. actually decreased with increase in air velocity.

The net conclusion from this research was that the wind-brake principle would give fairly good characteristics over a



FIG. 7. TYPE FA-4-A, VARIABLE-PITCH AIR FAN

limited range of air speed, and with further refinement it might have been worth putting into production. However, that stage was never reached, due to the work on the pivoted blade type of fan described below.

Friction-Clutch and Friction-Brake Fans. As in the types of regulating air fans discussed above, the friction-clutch and friction-brake principles of operation are inherently objectonable on account of their low efficiency and consequent high head resistance. They offered a possible solution, however, and were tried out experimentally. In the friction-clutch type of fan the fan hub is capable of free rotation about the shaft of the generator, which it drives through a friction clutch. The clutch is released by the action of centrifugal weights when the speed passes the predetermined maximum, permitting the fan to run at higher speed than the driven shaft of the generator. The curve of this fan was satisfactory for the first model, but the heating due to slipping of the clutch at high velocities was too great to permit the use of the fan in practice and the development was abandoned.

In the friction-brake type of fan the fan is keyed to the generator shaft and is prevented from exceeding normal speed by a brakeshoe operated by a centrifugal weight and bearing on a plate attached to the generator frame. This also was tried and gave results essentially similar to those obtained with the clutch type. With the very considerable variation in air speed met with on airplanes, the friction devices generated so much heat that their use was impossible.

Variable-Pitch Air Fans. The ideal principle for the design of a regulating air fan is that of varying the pitch of the blades to correspond to the variation in air speed; this prin-



FIG. 8. PERFORMANCE CURVES OF TYPE FA-4-A AIR FAN
(Diam. 20 in.; pitch variable)

ciple is by no means new, having been considered in a variety of forms for propellers for a number of years. The great difficulty in actual construction has been that the mechanical strength necessary to withstand the very high centrifugal forces and the delicacy of operation necessary for close regulation are very hard to combine.

This objection does not apply so forcibly to fans using very thin blades which are expected to warp under centrifugal action to change the pitch and a few samples which it was hoped would operate on this principle were tested. They were unsuccessful principally on account of mechanical construction and improved samples were never made up. The method is in any case of doubtful utility, since it can probably take care of only limited variations in speed, whereas the pivoted blade fans are capable of regulating over the widest variations in air speed likely to be met with in airplane practice.

Pivoted-Blade Air Fans. The earliest pivoted-blade fan to come to the attention of the Radio Development Section was made by the Sperry Gyroscope Company, but it proved unsuccessful, due to mechanical weakness. It was, however, the forerunner of very successful fans and serves to illustrate the general principle on which all operate. The blades are mounted on bearings and are capable of rotating through a considerable angle. Centrifugal weights are mounted on arms at-



FIG. 9. TYPE FA-8 VARIABLE-PITCH AIR FAN, SINGLE-BLADE, 200-WATT

tached to these blades and tend to turn them in the proper direction to increase the pitch. A resisting spring and necessary hub complete the mechanism.

The first model to perform satisfactorily was designed by

Mr. Thomas Slate, of the American Mechanical Improvement Company, of Washington, D. C. The very great improvement over the fixed-blade fans then in use made the production of this fan highly desirable, and it was undertaken at once under purchase specifications as follows:

Operating air-speed limits	45 to 300 m.p.h
Normal speed	4500 r.p.m.
Speed variation less than	Plus or minus 4%.
Overspeed test	8000 r.p.m.

It was, of course, realized that this fan was by no means in its final form, and work toward improving it and providing new sources of production was carried on as rapidly as possible. One of the objections to the original design was that the particular mechanism used caused the centrifugal force to increase as the sine of twice the angle, while the spring restraining force increased according to a straight-line relation. In the second successful design this was corrected by the use of a special linkage between spring and blade, which modified the curve of spring resistance to fit that of the centrifugal weight. Fig. 7 shows one of these fans and Fig. 8 its performance. In this, as in many other cases of radio development work, the design was conceived and outlined by the Signal Corps engineers and the details worked out at once by the manufacturer (in this case the American Propeller and Manufacturing Company) in a form ready for immediate production.

The third successful design of variable-pitch air fan was the work of Mr. Pinaud, of the Des Lauriers Aircraft Corporation, and differs very radically from those previously



FIG. 10. PERFORMANCE CURVES OF TYPE FA-8 AIR FAN
(Swept diam., 20 in.; pitch variable)

described. It uses only one blade and its principal advantage is that by ingenious counterbalancing practically all strain is taken off the bearings, whereas in other forms the thrust bearings must carry a very considerable load—both radial and thrust—due to the high speed of rotation and the unbalanced designs of the blades. Friction, of course, results in considerable "lag" in the performance of the fan. The mechanical construction of the Pinaud fan is also a considerable improvement over its predecessors in simplicity and ease of manufacture. Figs. 9 and 10 show its construction and performance.

Head-Resistance Tests

A demonstration of the value of the regulating air fans in reducing head resistance was made by the direct test of a complete radio-telegraph transmitting set in the wind tunnel. A run was first made with the set equipped with a fan hub and nose cap, but no blades; then a second run was made with a fan operating normally with the generator both loaded and running light, and finally a third run was made with the fan blades locked at several values of pitch. The results of these tests are shown in Fig. 11, from which the following conclusions may be drawn:

The head resistance of the set fully loaded in an air stream of 75 miles per hour is 6.5 lb. At this air speed the resistance of the blades alone equals the resistance of the body, after which the resistance of the blades remain nearly constant, while that of the body increases as the square of the air speed. The body alone has 5 lb. head resistance at an air speed of 90 miles per hour, and at the usual ratio ⅛ h.p. from the engine per lb. of head resistance, this requires 0.36 h.p. from the engine. On a basis of 20 lb. in the fuselage per h.p. from the engine, the set would weigh 13 lb. more than it now does and still be no more load on the engine, provided it was mounted in the fuselage and obtained its power directly from the engine. This emphasizes the desirability already mentioned of obtaining all electric power by direct drive from the engine rather than from air fans where it is possible to do so.

Airfoil Tests on Blades for Regulating Air Fans

In designing blades for regulating air fans the effect of wind pressure in producing torque around the blade axis has been questioned, and obviously such an effect might seriously interfere with the performance of the fan. To obtain data on this point tests were made on blades from a fan of the type shown in Fig. 7, using an airfoil balance.

The results thus obtained show that this effect is negligible so far as practical designing is concerned.



FIG. 11. HEAD-RESISTANCE CURVES, TYPE FA-4, AIR FAN

The Fate of the R-38

On Oct. 22, in the House of Commons, Lieut.-Col. Moore-Brabazon asked whether Great Britain had made any arrangements with the American government for the building of a rigid airship in England for the United States Navy.

Major-General Seely, Under-Secretary of State for Air replied: Arrangements have been made between the United States Navy and the Air Ministry by which the Airship R-38 embodying the newest features in design and construction will be completed without delay. The vessel will be handed over to United States Naval personnel on completion, and will proceed to America with her American crew as soon as the shed to house her is ready.

French Practice in Airship Construction

Abstract by John Jay Ide, Lt. (j.g.), U. S. N. R. F.

Specification for Seams of Envelopes—Envelope fabric overlaps ½ in. at seams. Stitching is in two rows ¼ in. apart, seven or eight stitches to the inch. The shuttle stitch is used.

One single-ply fabric strip 1⅛ in. wide of same color as exterior of envelope is cemented over exterior seam.

One single-ply raw white linen strip 1⅛ in. wide is cemented over interior seam. The strip is coated with unvulcanized rubber on the side next to seam. Over this is cemented another strip 1½ in. wide of single-ply fabric. This is rubberized on the gas side.

In kite balloons only one interior strip is used, but this is of 2-in. width. The envelope fabric overlaps ¼ in. instead of ½ in. The two rows of stitching, however, remain ¼ in. apart.



FIG. 1. SKETCH OF SEAM

Each covering strip has its warp and weft, parallel and perpendicular, respectively, to its length, whereas the envelope has biased warp and weft. (See Fig. 1.)

Precautions Taken Against Explosion When Filling Dirigibles—Following are instructions used for inflating airships:

Do not allow pressure of balloon to drop below three-tenths of an inch (difference between the two levels of manometer).

After the hydrogen cylinders are connected to the balloon through copper tubes, manifold and inflation lead, observe the following order of operations to empty the cylinders: First. Open the valves on the manifold branches. Second. Open the main manifold valve. Third. Open the valves on the gas cylinders.

After cylinders are considered to be empty wait two minutes, and then: First. Shut the main manifold valve. Second. Shut the valves on the manifold branches. Third. Shut the valves on the gas cylinders. Do not touch anything else.

If the pressure drops below three-tenths of an inch, empty at first three cylinders. If the pressure continues to fall, empty the other three cylinders.

The objects of the precautions taken in filling dirigibles are: (*a*) Avoidance of combination of air and hydrogen to prevent explosive mixture and to avoid the reduced lift of gas mixed with air. (*b*) Elimination of fire hazard.

These objects are attained by: 1. General plant layout. 2. Design of inflating lead and connections. 3. Design of manifold and connections. 4. Procedure with dirigible envelope. 5. Procedure with fabric inflating lead and connections. 6. Procedure with compressed hydrogen cylinders. 7. Electric lights and switches. 8. Conduct of personnel. 9. Fire-quenching means.



FIG. 2. SKETCH OF UNION

As to general layout there are two French schools of practice. In one the manifold is placed at a distance from the hangar, the fabric-filling tube being from 150 to 300 ft. long. The idea is that in case of fire at the manifold the fire may not reach the hangar and dirigible. In the other school the filling tube is as short as possible, on the theory that with proper precautions fire hazard is eliminated and that a long filling tube is likely to take in more air (at connections, etc.) than a short tube. In either case the manifold is placed outside the hangar.

The fabric inflating lead is about 6 in. in diameter and very slightly bell-mouthed at the ends where attached to connections. Only one inflating lead is used. Unions are slightly tapered so that the flared mouths of the inflating lead fit over them snugly and are in tight contact with each union for a couple of inches of length. (See Fig. 2.)

The manifold, of the simplest possible type, is of solid cast brass or bronze with six branches. The inside diameter is about 0.8 in. The dead end of the manifold should be solid, not a mechanical or welded joint. The inflation tube end should have the slightly tapered shape described for unions. This end of the manifold is provided with a simple, but positive, main valve. Each of the six manifold branches and each hydrogen cylinder is provided with a valve smaller than that on the manifold but of similar design. Small, pliable copper tubes (0.16 to 0.2 in. inside diameter) connect the manifold branches, through suitable unions, with the hydrogen cylinders.

The envelope is flattened out as much as possible before inflation so that there is no residual air.

After the inflation tube has been connected up it is flattened as much as possible. The tube should never be connected with a fold in it, as hydrogen would escape through the crevices (adding to the fire hazard), or air would be admitted by means of injector action and diffusion, lessening the lift of the dirigible. (See Fig. 3.)

Prior to inflation, during a stoppage thereof, or after completion, the inflation tube is left connected, but should be tightly tied up at appendix and manifold.

FIG. 3. SKETCH OF DEFECTIVE CONNECTION

The hydrogen cylinder valves are never opened, except when attached to tubes connecting with manifold. If they were opened, the escaping hydrogen, expanding, would have a refrigerating effect, perhaps producing atmospheric electricity. It should be emphasized that when cylinders are empty their valves must be closed, and remain so to avoid presence of air on refill of cylinders.

The hangar is illuminated by incandescent electric lights protected against fire hazard in the most approved way. All switches and keys to the lights should be outside the main hangar hall, separated therefrom by a wall.

The usual precautions such as non-smoking, non-carriage of matches, etc., are observed by those working in the hangar. In addition, it is desirable that electric flashlights be turned on and off outside the hangar. If not, the flashlight must be held in the pocket while being turned on and off.

Open bags of dry sand are placed next to the inflation tube at its junction with the manifold and its entrance to the hangar. In case of fire or other accident the bag can be placed directly on the tube, thus flattening it and shutting off the gas flow; also dry sand is an excellent fire-quenching means.

Precautions Against Sparks from Atmospheric Electricity and Radio.—All metal parts of the radio equipment are sep-



1. The NC-4—Varnished with Valspar. A notable demonstration of Valspar as the supreme Varnish for seaplanes.

2. Vought VE-7—Major Schroeder stated that Valspar played an important part in his winning the New York-Toronto Air Derby.

3. The R-34—Propellers varnished with Valspar by order of Major Scott, her commander.

3A. The Valentine crew Valsparring the rear propeller of the R-34.

4. Lawson Airliner—Mr. Lawson said: "Valspar played no small part in the success of this giant airliner."

5. The Valentine ship making the first commercial delivery of varnish—New York to Allentown, Pa.

The world's famous aircraft are Valsparred

THROUGHOUT the great war, Valspar saw service as the varnish for the airplanes of America and the Allied Governments. During the past year the activities of peace have produced many notable aerial achievements, in all of which Valspar has played an important part.

Valspar's toughness, elasticity and waterproofness have made good in every trial of war and peace. It is the one varnish that can be absolutely depended upon under all conditions of air service.

VALENTINE'S
VALSPAR
The Varnish That Won't Turn White

VALENTINE & COMPANY
456 Fourth Avenue, N. Y.
Largest Manufacturers of High-grade Varnishes in the World
ESTABLISHED 1832
New York Chicago Boston VALENTINE'S VARNISHES (Trade Mark) Toronto London Amsterdam
W. P. FULLER & CO., San Francisco and Principal Pacific Coast Cities

arated from the bag by a distance of from 3 to 6 ft.; where attached to the bag they are suspended by cords of vegetable fiber giving such a gap.

Metal parts used inside the balloon, as in valves, etc., are so designed that no intermittent contacts are made. There must be no gaps between metal parts across which an electric charge could be transferred. The parts of metal hinges, for instance, must be in continuously good electrical contact, if they are in contact at all.

These precautions are laid down by the constructor of the airship. Other precautions are prescribed by the radio authorities.

Suspended vs. Diaphragm Type of Ballonet—The latter type is preferable.

Objections to suspended type:

(1) The ballonet tends to tear at point of suspension, therefore it must be made of heavier material than the diaphragm type.

(2) Repair of the ballonet is difficult, as its upper part cannot be reached by a man inside.

(3) The suspension system tends to deform the top of the main envelope.

Advantages of diaphragm type:

(1) There is no tendency to tear, therefore a light fabric may be used.

(2) Repair is a simple matter.

(3) There is no deformation of main envelope.

(4) There is less diffusion surface, hence less material and again a lighter ballonet.

(5) When empty, the thickness of two fabrics at the bottom of the envelope is interposed between the gas and atmosphere.

To prevent the shifting of the ballonet longitudinally a system of cord stays is used.

In the case of long ballonets, transverse non-rubberized silk curtains perforated with 1-in. holes are used. These curtains are attached at the top of the ballonet, but are free at the bottom. They do not impede the even distribution of air into all compartments of the ballonet on its change of volume; but they are effective in preventing surge of the air mass.

Sand vs. Water as Ballast—Water is preferable as ballast for the reason that sand is very likely to get into the motor and other apparatus, with a possibility of serious damage.

To the objection that water may freeze, it may be replied that a great part of the time airships do not operate under conditions where this may take place. If the airship does go into freezing weather or altitudes, wood alcohol or glycerine may be put into the water to lower its freezing point. Salt should never be used on account of destruction of fabric, etc.

Even sand, however, is preferable to lead or other solid ballast on account of damage done to the terrain by the latter. This, of course, does not apply to bombs as ballast when over enemy terrain.

Necessity for Independent Blower Unit—An independent blower unit is considered necessary for a small airship, as additional air may be needed when the balloon is drifting, when neither a main motor take-off nor a ventilator system can be used.

A 2 to 4 hp. gasoline blower engine is recommended for a small airship. In addition, there should be a ventilating funnel and tube, the flared mouth of which is just abaft the main propeller tip and preferably under the car.

For an airship of about 250,000 cu. ft. the main power plant should be in two or four units. Each of these units should be provided with a take-off, clutch and blower, to insure reliability.—*Aircraft Technical Note. Bureau of Construction and Repair, Navy Department.*

Air Mail Record

All load-carrying air plane records for the postal mail service were broken on Dec. 2 when a twin-motor De Haviland 4 plane devised by and manufactured for the Post Office Department, covered the distance between the air mail field at Washington and that at Belmont Park, New York—a distance of 218 miles in 1 hour, 34 minutes, with a mail load of nearly 30,000 letters weighing 630 pounds. The speed was at the rate of 138 miles an hour. The best previous record was on Sept. 19, when a single motor De Haviland carried 300 pounds of mail from Washington to New York at a speed of 123 miles per hour and the third best record was on October 1 when a Curtiss plane carried 348 pounds from New York to Washington at a speed of 118 miles per hour.

The twin-motor De Haviland today was piloted by Samuel C. Eaton, Jr., of Philadelphia, Pa., and left College Park at 11 A. M. arriving at Belmont Park at 12.34 P. M. The time of flight included two circles around the field for altitude before setting out on his course and was the first trip made by the plane in a regular carrying of the mail. This plane is perhaps the only twin-motored plane built in the United States which not only maintains the altitude under full load with one engine but actually climbs on one engine. In the opinion of the postal authorities it is the greatest forward step made in the development of a small weight-carrying plane. It eliminates the fire hazard by having the engines in the wings and away from the gasoline supplies and also it minimizes danger to the pilot for the same reason. The twin-motor De Haviland is a distinctive product of the postal service being outlined personally by the Second Assistant Postmaster General Otto Praeger. The details of construction were worked out by Mr. A. H. Flint, College Point, N. Y.

The plane will enable the Department to salvage several hundred thousands of dollars worth of De Haviland 4 war planes and parts as well as Liberty motors, the power plant being two six-cylinder Libertys of 200 hp. each which can be constructed almost entirely out of one 12-cylinder, 400 hp. Liberty. The plane can carry nearly double the mail load that is carried by the single motor De Haviland.



NEW CAPRONI, 7 PASSENGER THREE MOTORED CROSS COUNTRY AIRPLANE

(C) *Underwood and Underwood*

THE HOME INSURANCE COMPANY NEW YORK

ELBRIDGE G. SNOW, President

Home Office: 56 Cedar St., New York

AIRCRAFT INSURANCE

Against the Following Risks

1. FIRE AND TRANSPORTATION.
2. THEFT (Of the machine or any of its parts).
3. COLLISION (Damage sustained to the plane itself).
4. PROPERTY DAMAGE (Damage to the property of others).

SPECIAL HAZARDS

Windstorm, Cyclone, Tornado—Passenger Carrying Permit—Stranding and Sinking Clause—Demonstration Permit—Instruction Permit

AGENTS IN CITIES, TOWNS AND VILLAGES THROUGHOUT THE UNITED STATES AND ITS POSSESSIONS, AND IN CANADA, MEXICO, CUBA, PORTO RICO AND CENTRAL AMERICA

Aircraft, Automobile, Fire and Lightning, Explosion, Hail, Marine (Inland and Ocean), Parcel Post, Profits and Commissions, Registered Mail, Rents, Rental Values, Riot and Civil Commotion, Sprinkler Leakage, Tourists' Baggage, Use and Occupancy, Windstorm

STRENGTH REPUTATION SERVICE

WE HAVE NO MORE USED CANADIAN TRAINING PLANES

the 350 Canadian Training Planes purchased from the Imperial Munitions Board of Great Britain have been disposed of

the unprecedented demand for these "Canucks" by pilots who use them for commercial purposes exhausted our supply much earlier than we anticipated

a few practically new Canadian Training Planes have been released for sale and are now ready for immediate delivery

the fuselages, wings, landing gears, etc., are new and the OX-5 engines have been completely overhauled and are guaranteed

the price is $3000 f.o.b. Toronto

United Aircraft Engineering Corporation

SALES OFFICE

1018 So. WABASH AVENUE
CHICAGO

52 Vanderbilt Ave.
NEW YORK CITY

Contractors to the Army,
Navy and Air Mail Service

L W F Engineering Co., inc.,
College Point New York

Used on the new "VOUGHT" Flying Boat

U-press-it in the Centre to Remove

'U-press-it' on the sides to Replace

No Threads Required
Easily Removed

The Upressit Cap

Simple to Operate
Easily Replaced

The ideal closure for your RADIATOR or GAS TANK
Fine for aeroplanes because of light weight and less resistance

Price less than the ordinary cap and much neater in appearance

U. S. METAL CAP & SEAL CO. 103-105-107 West 13th St., New York

THOMAS-MORSE

Tandem 2-Seater, Type S-6

Equipped with 80 h. p. Le Rhone Engine.

High speed, 105 M. P. H.

Landing speed 35 M. P. H.

Climb 7,800 ft. in first ten minutes.



THOMAS-MORSE AIRCRAFT CORPORATION

ITHACA, N.Y. U.S.A.

HALL-SCOTT

Hall-Scott Type L6 Airplane Engines.

Lieut.-Colonel E. J. Hall, upon the orders of the Secretary of War, as shown in War Department General Orders No. 69, dated May 24th, 1919, was awarded the Distinguished Service Medal for exceptionally meritorious and conspicuous service rendered in the designing of the Liberty engine and subsequently in the adapting of the LeRhone engine to the American methods of production, and also in pushing to completion the American adaptation of the De-Haviland plane.

The mere fact that Lieut.-Colonel Hall is again associated with our company, taking an active interest in the design and production of Hall-Scott airplane engines, is a guarantee to our respective customers that they will receive a product entirely up to Hall-Scott standard, and second to none in the airplane market.

HALL-SCOTT MOTOR CAR COMPANY

West Berkeley, California

Sturtevant Model 5A—4½

Sturtevant
(REG. U.S. PAT. OFF.)

AIRPLANE ENGINES
HAVE BEEN FLYING FOR TEN YEARS

They are the product of skilled engineering and manufacturing experience running through three generations.

Latest types are now available

Our new Catalog, No. 259, will interest you

B. F. STURTEVANT COMPANY
HYDE PARK, BOSTON, MASSACHUSETTS

Members Manufacturers' Aircraft Association



a counterbalanced aviation crankshaft . . . .

Patented July 10th, 1917

one of the 18 different
models we are now making
for 14 aviation motor companies . . .
reduces vibration and eliminates bearing pressure

We have shipped 46,637 Aviation Crankshafts to January 16, 1919

THE PARK DROP FORGE CO. CLEVELAND, OHIO

ATLAS WHEELS

Are daily gaining in favor with manufacturers and pilots of aircraft because:

They Absorb Shocks
They Are Stronger
They Are More Reliable

Standard Sizes Carried in Stock

Inquiries and orders will receive prompt attention

THE ATLAS WHEEL COMPANY
Rockefeller Building
CLEVELAND - OHIO

JONES



AIRPLANE TACHOMETER

"Best by Test"

was designed especially for the United States Navy Department for use in the war.

We supplied the Navy Department with large quantities of these instruments and their splendid record of service under all conditions as demonstrated by the famous Trans-Atlantic flight of the N C 1—N C 3—N C 4 where the JONES AIRPLANE TACHOMETERS were standard equipment, has been highly commended by the Navy Department officials.

The mechanism is of the centrifugal type; the dial is black with radium graduations and pointer, and is calibrated in various speed ranges up to 5000 R. P. M.

JONES AIRPLANE TACHOMETER

is the lightest instrument of any type yet produced, and is geared to be driven at cam shaft or engine speed without extra attachment.

JONES HAND TACHOMETER



Carry one and you can note R. P. M. quickly, easily and accurately, wherever you happen to be. Invaluable about power plants, generating stations, turbines, engines, shaftings. A neat little instrument of precision, with uniformly spaced dial, in handsome morocco carrying case.

Send today for a report of test by United States Bureau of Standards and our new booklet on tachometers.

JONES MOTROLA, Inc.
29 W. 35th Street New York

THE ONLY SCREW HOLES IN THE WORLD

You drive the screw holes with a hammer in any material.

The screw holes are made for wood screws or machine screws to fit all sizes of screws. The head is removed and you leave a permanent screw hole.

The Stine Screw Holes Co.

Manufacturers

WATERBURY, CONN., U. S. A.

DEPARTMENT 1

Once a Screw Hole, Always a Screw Hole

The Biggest Little Thing in the World

Some of the Reasons Why Screw Holes Will Be Bought and Used and Not Become Dead Stock for Anyone

1—They can be used without damage to receiving material

2—They enable you to standardize to wood or machine screws in all material

3—They are made of brass and will not rust under atmospheric or moisture conditions.

4—ECONOMY—They save more time value than the holes cost.

5—You get them for nothing and are paid for using them when you count time saved.

6—Screw holes have been needed ever since the first screw was used.

7—Special tools are NOT needed in using them in any material.

8—They can be used in any place a screw can be used.

9—By using screw holes, screws can be used in many places, and in many materials where it is impossible to use screws without them.

10—These are the only ready-made screw holes in the world.

11—No special screws are needed. These screw holes fit any wood screw or machine screw now in stock.

12—They make the neatest possible job in any material.

13—Every store where screws are sold must carry them in stock, because the line of screws is not complete without screw holes for them.

14—Every shop and factory where screws are used must also have these screw holes to fit the screws.

15—They are endorsed by all dealers in screws and by all users of screws.

16—Screw holes are entirely new and the world supply is yet to be furnished.

17—This is a progressive Old World of ours, and every active person in it must adopt all improved methods, and all new articles that will help him keep in the front line of progress.

18—Be among the first to stock up in screw holes if you are a dealer in screws.

19—Be among the first to install screw holes in your shop or factory, as you begin to save money soon as you use them.

20—In spite of the high cost of brass, screw holes are yet cheap.

21—We are letting the world know that screw holes can now be secured, by means of extensive advertising in all the principal Trade Journals that have the largest circulation among dealers in screws as well as users of screws.

22—Do not let your customer ask you for screw holes before you have them in stock. BE A LIVE WIRE.

23—They make everlasting holes in any material.

24—They mean "Ping-No-More" screw holes.

25—They are the result of Necessity being The Mother of Invention.

26—Anyone who can drive a nail can use screw holes.

27—Send for a sample and convince yourself.

28—Mechanics who see them say, "What do you think of that?"

29—In fact there are NO REASONS why screw holes should NOT be used.

Each of these reasons are enough to sell Screw Holes. There are many other reasons.

Write at once for our handsome Color Card showing screw holes in various materials which will be sent on request, together with samples and price list.

TRADE YALE MARK

19D

—a guide to profit for everyone who has loads to be handled.

You need this new Yale Chain Block book for the clear, complete, concise information it contains on every angle of hoisting equipment.

It gives you complete data on:

Yale Spur-Geared Chain Blocks
Yale Screw-Geared Chain Blocks
Yale Differential Chain Blocks
Yale Electric Wire Rope Hoist
Yale Electric Chain Hoist
"Brown Hoist" Trolleys—Cranes

The Yale hoisting equipment described in Catalog 19D speeds up production—with increased *safety* to the operator. The unusually complete-maintenance data is of special interest to present users.

"From Hook-to-Hook a Line-of-Steel"

Let us send you your copy.

Ask your machinery supply house or wire for catalog on Yale Chain Blocks and Electric Hoists.

For a Factory Locking Equipment Use a Yale Master-Key System.

The Yale & Towne Mfg. Co.

9 East 40th Street New York City

SPRUCE LUMBER

for

Airplane Construction

FOR twenty years we have been exclusive manufacturers of PACIFIC COAST SPRUCE LUMBER. Our product is from the very best forests of SITKA SPRUCE.

We solicit your inquiries

MULTNOMAH LUMBER & BOX COMPANY

PORTLAND OREGON

Fahrig Anti-Friction Metal

The Best Bearing Metal on the Market
A Necessity for Aeroplane Service

Fahrig Metal Quality has become a standard for reliability. We specialize in this one tin-copper alloy which has superior anti-friction qualities and great durability and is always uniform.

When you see a speed or distance record broken by Aeroplane, Racing Automobile, Truck or Tractor Motor, you will find that Fahrig Metal Bearings were in that motor.

FAHRIG METAL CO., 34 Commerce St., N.Y.

For R.P.M. Readings During the Block Test

Before installing or after overhauling motors, get their accurate "rev." ratings with the instantly applied

Veeder
SPEED COUNTER



Press the tip of the Veeder against rear end of crank shaft—engaging the push-clutch the moment you start timing; releasing pressure when minute is up. The clutch starts or stops recording mechanism instantly, giving accurate R. P. M. readings without use of stop-watch. Price, $3.50

Veeder Counters are made for automatically recording the production of machines, and for hand-counting purposes, too. Write for the counter booklet

The Veeder Mfg. Co.
56 Sargeant St., Hartford, Conn.

The "Bristol" Aeroplanes

COMMERCIAL
—and—
SPORTING
TYPES

Inquiries for territorial representation invited

EVERY element of perfection in construction and design is incorporated in *"Bristol"* planes—

the result of ten years highly specialized research and practical development.

There is a "Bristol" for *your* purpose.

WILLIAM G. RANELS
— Representing —
THE BRITISH & COLONIAL AEROPLANE CO., Ltd.
512 Fifth Avenue New York

WAKEFIELD
Castrol
REGD. 'R'

Withstands extremes of heat and cold.

Is never too thick, never too thin, but always efficient under the most trying conditions.

C. C. WAKEFIELD & CO. Ltd.,
Wakefield House
CHEAPSIDE, LONDON, E.C. 2. ENG.

PROPELLERS

Quartered Oak Laminated Construction. Built up and shaped strictly in accordance with Government Drawings and Specifications.

Not One Rejection By The Government

WE CARRY IN STOCK

For *Hispano Suiza*, J.N.6-H. No. 1 Engine. Dia. 8′ 6″. Pitch 5.76 @ 2/3 R. 150 H.P. Pig Skin or Copper Tips. Govt. Blue Print 34889.

For *Curtiss* OX-5 Engine. 90 Horsepower. Diameter 8′. Pitch 5′. Copper Tipped only. Government Blue Print 13706.

Write for prices

BUY THE BEST
AMERICAN SASH & DOOR COMPANY
KANSAS CITY, MO.

Aluminum Company of America
General Sales Office, 2400 Oliver Building
PITTSBURGH, PA.

Producers of Aluminum

Manufacturers of

Electrical Conductors
for Industrial, Railway and Commercial Power Distribution
also
Ingot, Sheet, Tubing, Rod, Rivets, Moulding, Extruded Shapes
also
Litot Aluminum Solders and Flux

CANADA
Northern Aluminum Co., Ltd., Toronto
ENGLAND
Northern Aluminium Co., Ltd., London
LATIN AMERICA
Aluminum Co. of South America, Pittsburgh, Pa.

FUEL LEVEL GAGES

This cut shows our Model 51 Gage which is standard on practically all type of military training machines.

Other types of gages in large quantities are "doing their bit" as part of the equipment of English Government Warplanes.

SPECIAL TYPES DESIGNED FOR YOUR ESPECIAL NEEDS

BOSTON AUTO GAGE CO.
8 WALTHAM STREET, BOSTON, MASS.

ROEBLING
AIRCRAFT WIRE
STRAND AND CORD
THIMBLES AND FERRULES
Send for Catalogue
JOHN A. ROEBLING'S SONS CO.
TRENTON, N. J.

Miessner Airfones
and
Simon Radio Apparatus
for
all aircraft uses

EMIL J. SIMON
217 Broadway New York City

Half of the American airmen have proved the Berling's worth.

Berling Magneto
WORTH MORE DOES MORE

NEW AND USED AIRPLANES AND MOTORS

Offer, among others, the following Seaplanes and Flying Boats
Curtiss JN4 Seaplane
Thomas Seaplane
Standard Seaplane
Aeromarine Seaplane
Curtiss Flying Boat
Thomas Flying Boat
USAC twin motored 4 passenger flying boat and others
Land machines
Tractor biplanes
Aeronautical motors
30 to 300 HP.
Send for lists "AN"
State your needs
Cable Address: USAE, New York
Long Distance Phone: Cortlandt 449

U.S. AERO EXCHANGE 38 PARK ROW NEW YORK CITY

QUALITY INSTRUMENTS FOR AIRPLANES

FOXBORO
TRADE MARK

Indicating Dial Type Thermometers for circulating oil and water.
Airspeed Indicators to determine buoyancy and avoid stalling.
Oil Pressure Gauges
Air Pressure Gauges



The Foxboro line includes many other types of Indicating and Recording Instruments designed for all sorts of conditions and purposes.

Bulletin No. BI-110 describes our Airplane Instruments.

THE FOXBORO CO., Inc., FOXBORO, MASS., U. S. A

New York Chicago Philadelphia Pittsburgh Peacock Bros. Montreal, Canada Birmingham San Francisco

DOEHLER DIE-CASTINGS

are made by the
WORLD'S LARGEST
Manufacturers of Die-Castings

DOEHLER DIE-CASTING CO.

MAIN OFFICE AND EASTERN PLANT BROOKLYN, N.Y.
WESTERN PLANT TOLEDO, OHIO.

SALES OFFICES IN ALL PRINCIPAL CITIES



The pioneer manufacture of airplane parts made from bar stock. Any and everything pertaining to the manufacture of airplanes.

Any Quantity

A. J. MEYER MANUFACTURING CO.
819 John Street West Hoboken, N. J.

"The Propeller That Beats Them All"

Specially designed for Curtiss Airplanes, O. X. 5 Motors; it climbs 2000 ft. in five minutes with full load; it adds 10 miles per hour flying speed. Hundreds of them already in use. Some Airplanes are being fitted with three seats to utilize the enormous power of this propeller. These propellers are carried in stock; ready for immediate delivery. Price, $50.00 for plain tips; $70.00 with metal tips, F. O. B.

Airplanes rebuilt; repaired; spare parts; supplies

JACUZZI BROTHERS
1450 SAN PABLO AVENUE, BERKELEY, CALIFORNIA
(Contractors of propellers for the United States Government)

Flottorp Manufacturing Co.

AIRCRAFT PROPELLERS
Established 1912

213 Lyon St., Grand Rapids, Michigan

Contractors to United States Government

FREDERICK W. BARKER

REGISTERED PATENT ATTORNEY

2 RECTOR STREET NEW YORK

Telephone 4174 Rector *Over 30 Years in Practice*

PRESIDENT
AERONAUTICAL SOCIETY OF AMERICA
FROM 1915 TO 1919

SPECIALTY: Patent Claims That Protect

AIRPLANES——DEVELOPERS OF SPECIAL AIRCRAFT——SEAPLANES

WITTEMANN-LEWIS AIRCRAFT COMPANY, Inc.

NEWARK BUILDERS SINCE 1906 NEW JERSEY

EVERY Liberty Aircraft Engine built is equipped with Zenith Liberty Carburetors—*the reason is clear to Zenith users.*

Zenith Carburetor Co.
New York DETROIT Chicago

LEARN TO FLY

in old established school, under an instructor who has given instruction to more

AMERICAN ACES

than any other instructor.

Army Training Planes Used.
We Build Our Machines.

PRINCETON FLYING CLUB, Princeton, N. J.
WEST VIRGINIA AIRCRAFT CO., Wheeling, W. Va.
DAYTONA FLYING CLUB (Winter), Daytona, Fla.

HARTSHORN STREAMLINE WIRES

ASSEMBLED WITH HARTSHORN
UNIVERSAL STRAP ENDS

MAKE THE IDEAL AEROPLANE TIE RODS

All streamline wires heat treated in process and produced by our carefully developed method of cold reverse rolling, will meet the most exacting tests.

Send for our descriptive circular A-1, describing our wires and terminal fittings

STEWART HARTSHORN CO.
250 FIFTH AVENUE, NEW YORK

AIRPLANE INSURANCE

FOR THE

Manufacturer—Flyer

Fire—Collision—Damage to Property of Others
Legal Liability—Life—Personal Accident
Conservative Rates—Best Companies

PHONE—WRITE—WIRE

HARRY M. SIMON
Insurance Expert
81 Fulton Street New York, N. Y.

PHILBRIN
DUPLEX IGNITION
—with a second system to spur the motor to super-service.

COMBINES two separate and distinct systems in one—a Single Spark System, most economical of gas, and offering vastly increased power. A Secondary or High Frequency System which delivers to each cylinder a stream of a thousand sparks a second—overcomes abnormal conditions, such as foul spark plugs, poor fuel, poor carburetion, and cold cylinders—offers 100% Assurance against ignition failure.

Easy to install, moderate in price. Descriptive catalogues and our special sales proposition on request.

PHILIPS-BRINTON COMPANY
501 So. Broad Street Kennett Square, Pa.

CAPITAL INTERNAL GRINDER **STAMPINGS** JIGS TOOLS DIES

WE realize *in air* or *at sea* there should be *no faulty* material. All machine parts must be made *right* and perform their functions *properly*, hence we have equipped our new plant to turn out work of the highest quality. We offer our facilities to you and trust we may be of service.

Will you give us a trial?

LANSING STAMPING & TOOL CO.
LANSING, MICHIGAN

CLASSIFIED ADVERTISING

10 Cents a word, minimum charge $2.00, payable in advance. Address replies to box numbers, care AVIATION AND AERONAUTICAL ENGINEERING, 22 East 17th Street, New York.

FOR SALE—Two passenger Biplane, 36 ft. Wings, 7 cyl. Gnome Motor. All surfaces newly covered. Price $1500.00, best flying condition. C. H. Rutherford, First & C. Sts., San Diego, Calif.

WANTED—Partly or completely wrecked JN-4 machine to be used for demonstration purposes. Will accept in any condition. Address 1205 East 2nd St., Tulsa, Okla.

FOR SALE—Farman Biplane 80 H. P. Renault air-cooled motor. Flown less than ten hours, fully equipped and in perfect condition. Bargain to immediate purchaser. Address W. Wallace Kellett, 1 West 34th Street, New York City.

INDEX TO ADVERTISERS

A

Aeromarine Plane & Motor Co. ... 377
Aircraft Journal ... 402
Aluminum Castings Company ... 415
Aluminum Company of America ... 410
American Propeller & Mfg. Co. ... 409
Atlas Wheel Co. ... 407

B

Barker, F. W. ... 411
Berling Magneto ... 410
Boston Auto Gage Co. ... 410
British and Colonial Aeroplane Co., Ltd. ... 409

C

Curtiss Aeroplane & Motor Corp ... 417

D

Daytona Flying Club ... 412
Doehler Die-Casting Co. ... 411

F

Farman H & M ... 376
Fahrig Metal Co. ... 408
Flottorp Mfg. Co. ... 411
Foxboro Co., The ... 411

H

Hartzell Walnut Propeller Co. ... 378
Hall-Scott Motor Car Co. ... 405
Home Insurance Co. ... 403

J

Jacuzzi Bros. ... 411
Jones Motrola, Inc. ... 407

L

L-W-F Engineering Co., Inc. ... 404
Lansing Stamping & Tool Co. ... 412
Lewis & Vought, Inc. ... 375

M

Martin, The Glenn L. Co. ... 374
Meyer, A. J. Mfg. Co. ... 411
Multnomah Lumber and Box Co. ... 408

N

New Departure Mfg. Co. ... 380

P

Park Drop Forge Co. ... 406
Philips-Brinton Co. ... 412
Pioneer Instrument Co. ... 412
Princeton Flying Club ... 412

R

Roebling's Sons Co., John A. ... 410

S

Simon, Harry M. ... 412
Simon, Emil J. ... 410
Stine Screw Holes Co. ... 408
Sturtevant Co., The B. F. ... 406
Stewart Hartshorn & Co. ... 412

T

Thomas-Morse Aircraft Corp. ... 405

U

Union Gas Engine Co. ... 414
United Aircraft Engineering Corp. ... 403
U. S. Aero Exchange ... 410
U. S. Metal Cap & Seal Co. ... 404

V

Valentine & Co. ... 401
Veeder Manufacturing Co. ... 409
Vought, Chance M. ... 375

W

Wakefield and Co., C. C. ... 409
West Virginia Aircraft Co. ... 412
Wittemann-Lewis Aircraft Co. ... 411
Wright-Martin Aircraft Corp. ... 394-395
Wyman-Gordon Co. ... 379

Y

Yale & Towne Mfg. Co. ... 408

Z

Zenith Carburetor Co. ... 412

A United States
Naval Officer Says:



Micrograph of section of *Lynite* Piston, showing close-grained structure of metal.

Micrograph of section of piston made from same alloy but by sand-casting process.

The Camera Doesn't Lie

To the eye, two aluminum alloy pistons may look just about alike, but put them under the searching gaze of the microscope and surprising differences are likely to appear.

The illustrations above are micrographs of sections of two pistons, one made by the ordinary sand-casting method, the other by the permanent-mold process, used in making *Lynite* Pistons.

The same alloy was used in each case and the sand-cast piston is probably better than average, yet it takes but a glance to see how much finer the grain and more closely knit the structure of the permanent-mold piston.

The finer grained structure is due to the rapid cooling during solidification which results in a better dispersion of the copper aluminum compound. This makes the piston wear much longer at every point, on the skirt, on the wrist-pin bosses and around the ring-grooves. Another operating advantage of *Lynite* Pistons is freedom from hard spots, eliminating danger of scratched cylinders.

Lynite Pistons also have a number of advantages in manufacturing. Less metal has to be removed in machining because thay can be cast to closer dimensions. Freedom from hard spots makes possible greater machining speed because less trouble is encountered with dulled tools and, furthermore, fewer castings have to be rejected.

Absence of blow-holes and dimensional defects also play a considerable part in cutting down the number of scrapped pistons, reducing machining time and cost, and speeding up production.

THE ALUMINUM CASTINGS COMPANY
LYNITE and LYNUX Products
General Office: 6205 Carnegie Avenue, Cleveland
District Sales Offices:
New York · 511 Fifth Ave. Detroit Jos. Campau and Dun Rd.
Cleveland 6523 Euclid Ave. Chicago · · 1640 Conway Bldg.

LYNITE



ROLAND ROHLFS AND THE CURTISS "WASP"

"Farthest Up"

THE internationally famous Curtiss "Wasp" Triplane—established the world's record on September 18 by attaining a height of 34,610 feet—more than six miles in the air, guided by Roland Rohlfs, test-pilot.

"Farthest North" and "Farthest South" have been attained by brave explorers, but "Farthest Up" mastery of the air—has constantly tempted human skill and courage.

Curtiss achievement has brought us "nearest the sun" of aircraft-perfection. The recognized safety and efficiency of Curtiss products result from the highest ideals and constant scientific efforts towards perfection.

CURTISS AEROPLANE and MOTOR CORPORATION

Sales Offices: Room 1456, 52 VANDERBILT AVENUE, NEW YORK

CURTISS ENGINEERING CORPORATION
GARDEN CITY, L. I.

THE BURGESS COMPANY
MARBLEHEAD, MASS.

CURTISS FLYING STATION OF ATLANTIC CITY, INC., ATLANTIC CITY, NEW JERSEY

Gentlemen: Please mail me at once, your special Curtiss JN proposition—showing commercial uses.

Name_____

Address_____

City_____ State_____





TWO VIEWS OF THE BAROGRAPH RECORD

Curtiss

Member Manufacturers' Aircraft Association